



RAVEN

POWDER FREE NITRILE GLOVES

- Powder Free Nitrile Gloves
- Superior Puncture & Abrasion Resistance
- Latex Free
- Textured Grip
- Ambidextrous



6 mil
NITRILE

P/N	Size
66516	Small
66517	Medium
66518	Large
66519	X-Large
66520	XX-Large



100 Gloves by Weight

RAVEN

POWDER FREE NITRILE GLOVES



Specification of Nitrile Gloves

Test On	Particular		Specification	In-House Inspection
				Level / AQL.
Dimension mm, in.	Width	Small	85±5mm, 3.35±0.2in	S 2 / AQL 4.0
		Medium	95±5mm, 3.74±0.2in	
		Large	105±5mm, 4.13±0.2in	
		X-Large	115±5mm, 4.53±0.2in	
		XX-Large	120±5mm, 4.72±0.2in	
	Length		245±5mm, 9.65±0.2in	
	Thickness (Singlewall)	Cuff (25mm, 0.9843in from bead)	0.13mm, 0.0051in	
Palm (Center of palm)		0.15mm, 0.0059in		
Finger (13mm, 0.5118in from tip)		0.17mm, 0.0067in		
Tensile properties	Before Aging	Tensile Strength	min 14 Mpa	S 2 / AQL 4.0
		Elongation at break	min 500 %	
		Force at break	min 7.5 N	
	Aged 100±2C° 212±35.6F° For 24 hrs.	Tensile Strength	min 14 Mpa	
		Elongation at break	min 500 %	
		Force at break	min 5.5 N	
Freedom from Holes				GI / AQL 1.5
Visual Defects (Major)	Lump = 2 mm, 0.08in Drit = 1.5mm, 0.059in, Sticky Pleat = 5mm, 0.2in Sticky Visible Hole (Non-inflated) Discoloration, Mix Surface, Incomplete Bead, Wrong Orientation, Poor Donning			GI / AQL 2.5
Visual Defects (Minor) Visible at < 2 ft)	Lump < 2 mm, 0.08in Drit < 1.5mm, 0.059in, Sticky Pleat < 5mm, 0.2in Rolled Bead			GI / AQL 4.0
Powder-Free	Polymer coated			