

1 Identification

- **Product identifier**
- **Trade name:** 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics
- **Article number:** 3305, 3306, 3307
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Manufactured for: IAMG International Autobody Marketing Group, 1505 North Hayden Road, Ste.111, Scottsdale, AZ 85257
Information phone : 480.451.4451
- **Information department:** 1-87-REFINISH
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222

Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas

H280

Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 1A

H350

May cause cancer.

Repr. 2

H361

Suspected of damaging fertility or the unborn child.

STOT SE 2

H371-H336

May cause damage to organs. May cause drowsiness or dizziness.

STOT RE 2

H373

May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2

H315

Causes skin irritation.

Eye Irrit. 2A

H319

Causes serious eye irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)
USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Quartz (SiO₂)
toluene
acetone
titanium dioxide

· **Hazard statements**

H222 *Extremely flammable aerosol.*
H280 *Contains gas under pressure; may explode if heated.*
H315 *Causes skin irritation.*
H319 *Causes serious eye irritation.*
H350 *May cause cancer.*
H361 *Suspected of damaging fertility or the unborn child.*
H371-H336 *May cause damage to organs. May cause drowsiness or dizziness.*
H373 *May cause damage to organs through prolonged or repeated exposure.*

· **Precautionary statements**

P210 *Keep away from heat/sparks/open flames/hot surfaces. No smoking.*
P251 *Do not pierce or burn, even after use.*
P260 *Do not breathe dust/fume/gas/mist/vapors/spray.*
P211 *Do not spray on an open flame or other ignition source.*
P280 *Wear protective gloves.*
P280 *Wear eye protection / face protection.*
P264 *Wash thoroughly after handling.*
P270 *Do not eat, drink or smoke when using this product.*
P201 *Obtain special instructions before use.*
P202 *Do not handle until all safety precautions have been read and understood.*
P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
P321 *Specific treatment (see on this label).*
P308+P313 *IF exposed or concerned: Get medical advice/attention.*
P332+P313 *If skin irritation occurs: Get medical advice/attention.*
P337+P313 *If eye irritation persists: Get medical advice/attention.*
P314 *Get medical advice/attention if you feel unwell.*
P302+P352 *IF ON SKIN: Wash with plenty of water.*
P362+P364 *Take off contaminated clothing and wash it before reuse.*
P405 *Store locked up.*
P410+P403 *Protect from sunlight. Store in a well-ventilated place.*
P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.*
P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)
USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMS-ratings (scale 0 - 4)**

HEALTH	*1	Health = *1
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* **3 Composition/information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

- **Dangerous components:**

68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
67-64-1	acetone	13 - 30%
14808-60-7	Quartz (SiO ₂)	13 - 30%
1330-20-7	xylene	10 - 13%
110-19-0	isobutyl acetate	10 - 13%
108-88-3	toluene	1.5 - 5%
123-86-4	n-butyl acetate	1.5 - 5%
13463-67-7	titanium dioxide	1.5 - 5%
78-93-3	butanone	1.5 - 5%
14807-96-6	Talc	≤1%

* **4 First-aid measures**

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* **5 Fire-fighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**
*Wear self-contained respiratory protective device.
Mouth respiratory protective device.*

* **6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**
*Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.*
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**
*Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.*
- **Reference to other sections**
*See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.*

* **7 Handling and storage**

- **Handling:**
- **Precautions for safe handling**
*No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.*
- **Information about protection against explosions and fires:**
*Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** *Store away from oxidizing agents.*
- **Further information about storage conditions:** *Keep receptacle tightly sealed.*

(Contd. on page 5)
USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 4)

- **Specific end use(s)** No further relevant information available.

*** 8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 1187 mg/m³, 500 ppm

Long-term value: 594 mg/m³, 250 ppm

BEI

14808-60-7 Quartz (SiO₂)

PEL see Quartz listing

REL Long-term value: 0.05* mg/m³

*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³

*as respirable fraction

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm

Long-term value: 434 mg/m³, 100 ppm

BEI

110-19-0 isobutyl acetate

PEL Long-term value: 700 mg/m³, 150 ppm

REL Long-term value: 700 mg/m³, 150 ppm

TLV Short-term value: NIC-712 mg/m³, NIC-150 ppm

Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500* ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 75 mg/m³, 20 ppm

BEI

123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm

Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: (950) NIC-712 mg/m³, (200) NIC-150 ppm

Long-term value: (713) NIC-238 mg/m³, (150) NIC-50 ppm

(Contd. on page 6)

USA

Printing date 11/02/2015

Reviewed on 11/02/2015

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 5)

78-93-3 butanone

PEL Long-term value: 590 mg/m³, 200 ppm

REL Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm

TLV Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI

· **Ingredients with biological limit values:**

67-64-1 acetone

BEI 50 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

108-88-3 toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

78-93-3 butanone

BEI 2 mg/L
Medium: urine
Time: end of shift
Parameter: MEK

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 7)

USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 6)

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Aerosol

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

55 °C

· **Flash point:**

-103 °C

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

405 °C

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

(Contd. on page 8)

USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 7)

- **Danger of explosion:** *In use, may form flammable/explosive vapour-air mixture.
Avoid high heat*
- **Explosion limits:**
 - Lower:** 1.1 Vol %
 - Upper:** 13.0 Vol %
- **Vapor pressure at 20 °C:** 233 hPa
- **Density at 20 °C:** 0.8163 g/cm³
- **Relative density** *Not determined.*
- **Vapor density** *Not determined.*
- **Evaporation rate** *Not applicable.*
- **Solubility in / Miscibility with Water:** *Not miscible or difficult to mix.*
- **Partition coefficient (n-octanol/water):** *Not determined.*
- **Viscosity:**
 - Dynamic:** *Not determined.*
 - Kinematic:** *Not determined.*
- **Solvent content:**
 - Organic solvents:** 77.4 %
 - VOC content:** 57.5 %
590.7 g/l / 4.93 lb/gl
- **Solids content:** 22.6 %
- **Other information** *No further relevant information available.*

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:**
 - Nitrogen oxides*
 - Hydrocarbons*
 - Carbon monoxide and carbon dioxide*

*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
 - 1330-20-7 xylene**
 - Oral LD50 4300 mg/kg (rat)
 - Dermal LD50 2000 mg/kg (rabbit)

(Contd. on page 9)
USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 8)

108-88-3 toluene

Oral LD50 5000 mg/kg (rat)
Dermal LD50 12124 mg/kg (rabbit)
Inhalative LC50/4 h 5320 mg/l (mouse)

• **Primary irritant effect:**

• **on the skin:** Irritant to skin and mucous membranes.

• **on the eye:** Irritating effect.

• **Sensitization:** No sensitizing effects known.

• **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

• **Carcinogenic categories**

• **IARC (International Agency for Research on Cancer)**

14808-60-7 Quartz (SiO ₂)	1
1330-20-7 xylene	3
108-88-3 toluene	3
13463-67-7 titanium dioxide	2B
14807-96-6 Talc	2B
7631-86-9 silicon dioxide, chemically prepared	3
1333-86-4 Carbon black	2B
111-76-2 2-butoxyethanol	3
100-41-4 ethylbenzene	2B

• **NTP (National Toxicology Program)**

14808-60-7 Quartz (SiO ₂)	K
---------------------------------------	---

• **OSHA-Ca (Occupational Safety & Health Administration)**

68911-87-5 ALKYL QUATERNARY AMMONIUM MONTMORILLONITE

12 Ecological information

• **Toxicity**

• **Aquatic toxicity:** No further relevant information available.

• **Persistence and degradability** No further relevant information available.

• **Behavior in environmental systems:**

• **Bioaccumulative potential** No further relevant information available.

• **Mobility in soil** No further relevant information available.

• **Additional ecological information:**

• **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• **Other adverse effects** No further relevant information available.

USA

(Contd. on page 10)

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

* 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT, IATA** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS

- **Transport hazard class(es)**

- **DOT**



- **Class** 2.1
- **Label** 2.1
- **ADR**



- **Class** 2 5F Gases
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1
- **Packing group**
- **DOT, ADR, IMDG, IATA** Void

(Contd. on page 11)
USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 11/02/2015

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 10)

- **Environmental hazards:**
- **Marine pollutant:** No
- **Special precautions for user** Warning: Gases
- **EMS Number:** F-D,S-U
- **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
- **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **DOT**
- **Quantity limitations** On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg
- **ADR**
- **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
- **IMDG**
- **Limited quantities (LQ)** 1L
- **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**
 - 1330-20-7 xylene
 - ACRYLIC RESIN
 - 108-88-3 toluene
 - 78-93-3 butanone
 - 14807-96-6 Talc
 - 111-76-2 2-butoxyethanol
 - 100-41-4 ethylbenzene
 - 67-56-1 methanol

(Contd. on page 12)
USA

Printing date 11/02/2015

Reviewed on 11/02/2015

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 11)

· **TSCA (Toxic Substances Control Act):**

68476-86-8 Petroleum gases, liquefied, sweetened
67-64-1 acetone
14808-60-7 Quartz (SiO₂)
1330-20-7 xylene
110-19-0 isobutyl acetate
108-88-3 toluene
123-86-4 n-butyl acetate
13463-67-7 titanium dioxide
78-93-3 butanone
14807-96-6 Talc
68911-87-5 ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
16883-83-3 benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate
7631-86-9 silicon dioxide, chemically prepared
21645-51-2 aluminium hydroxide
51274-00-1 YELLOW IRON OXIDE

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7 Quartz (SiO₂)
1330-20-7 xylene
13463-67-7 titanium dioxide
1333-86-4 Carbon black
100-41-4 ethylbenzene

· **Chemicals known to cause reproductive toxicity for females:**

108-88-3 toluene

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene
67-56-1 methanol

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1 acetone	I
1330-20-7 xylene	I
108-88-3 toluene	II
78-93-3 butanone	I
111-76-2 2-butoxyethanol	NL
100-41-4 ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1 acetone	A4
14808-60-7 Quartz (SiO ₂)	A2
1330-20-7 xylene	A4
108-88-3 toluene	A4

(Contd. on page 13)
USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 12)

13463-67-7 titanium dioxide	A4
14807-96-6 Talc	A4
1333-86-4 Carbon black	A4
111-76-2 2-butoxyethanol	A3
100-41-4 ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7 Quartz (SiO₂)
13463-67-7 titanium dioxide
1333-86-4 Carbon black
67-56-1 methanol

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

Quartz (SiO₂)
toluene
acetone
titanium dioxide

· **Hazard statements**

H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H371-H336 May cause damage to organs. May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P251 Do not pierce or burn, even after use.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P211 Do not spray on an open flame or other ignition source.
P280 Wear protective gloves.
P280 Wear eye protection / face protection.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321 Specific treatment (see on this label).
P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 14)

USA

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 13)

P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P302+P352	IF ON SKIN: Wash with plenty of water.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:** 1-480-451-4451
- **Date of preparation / last revision** 11/02/2015 / 18
- **Abbreviations and acronyms:**
ICAO: International Civil Aviation Organisation
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
Press. Gas: Gases under pressure: Compressed gas
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Carc. 1A: Carcinogenicity, Hazard Category 1A
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
- *** Data compared to the previous version altered.**