

1 Identification of substance

- **Product details**
- **Trade name:** 39693 Self Etching Primer Green
- **Article number:** 39693
- **Manufacturer/Supplier:**
SEM Products, Inc.
651 Michael Wylie Dr.
Charlotte, NC 28217
USA
(704)522-1006
- **Information department:** 24HR EMERGENCY CHEMTREC 800-424-9300

2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

68476-86-8	Petroleum gases, liquefied, sweetened	10-25%
67-64-1	acetone	10-25%
110-19-0	isobutyl acetate	2.5-10%
108-88-3	toluene	2.5-10%
141-78-6	ethyl acetate	2.5-10%
78-93-3	butanone	2.5-10%
9004-70-0	CELLULOSE NITRATE	2.5-10%
	MALEIC MODIFIED ROSIN RESIN	2.5-10%
14808-60-7	Quartz (SiO ₂)	2.5-10%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	2.5-10%
123-86-4	n-butyl acetate	≤ 2.5%
67-63-0	propan-2-ol	≤ 2.5%
1330-20-7	xylene	≤ 2.5%
1330-78-5	tris(methylphenyl) phosphate	≤ 2.5%
84-74-2	dibutyl phthalate	≤ 2.5%

3 Hazards identification

· **Hazard description:**



Toxic
Extremely flammable

· **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

Warning! Pressurized container.

May cause cancer by inhalation.

May cause harm to the unborn child.

Extremely flammable.

Irritating to eyes, respiratory system and skin.

Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

(Contd. on page 2)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 1)

Possible risk of harm to the unborn child.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

85.8 % by mass of the contents are flammable

Keep out of the reach of children.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 4

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *2

Fire = 4

Reactivity = 0

4 First aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 3)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 2)

Open and handle receptacle with care.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

68476-86-8 Petroleum gases, liquefied, sweetened

TLV Short-term value: 2950 mg/m³, 1000 ppm

67-64-1 acetone

PEL 2400 mg/m³, 1000 ppm

REL 590 mg/m³, 250 ppm

TLV Short-term value: 1782 mg/m³, 750 ppm

Long-term value: 1188 mg/m³, 500 ppm

BEI

110-19-0 isobutyl acetate

PEL 700 mg/m³, 150 ppm

REL 700 mg/m³, 150 ppm

TLV 713 mg/m³, 150 ppm

108-88-3 toluene

PEL Short-term value: C 300; 500* ppm

Long-term value: 200 ppm

*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

TLV 188 mg/m³, 50 ppm

Skin; BEI

141-78-6 ethyl acetate

PEL 1400 mg/m³, 400 ppm

REL 1400 mg/m³, 400 ppm

TLV 1440 mg/m³, 400 ppm

(Contd. on page 4)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 3)

78-93-3 butanone

PEL 590 mg/m³, 200 ppm
REL Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
TLV Short-term value: 885 mg/m³, 300 ppm
Long-term value: 590 mg/m³, 200 ppm
BEI

14808-60-7 Quartz (SiO₂)

REL 0.05* mg/m³
*Respirable dust
TLV (0.05 R) mg/m³
NIC-0.025 R

123-86-4 n-butyl acetate

PEL 710 mg/m³, 150 ppm
REL Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm
TLV Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

67-63-0 propan-2-ol

PEL 980 mg/m³, 400 ppm
REL Short-term value: 1225 mg/m³, 500 ppm
Long-term value: 980 mg/m³, 400 ppm
TLV Short-term value: 984 mg/m³, 400 ppm
Long-term value: 492 mg/m³, 200 ppm

1330-20-7 xylene

PEL 435 mg/m³, 100 ppm
REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm
(o-, m-, & p-isomers)
TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

84-74-2 dibutyl phthalate

PEL 5 mg/m³
REL 5 mg/m³
TLV 5 mg/m³

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 4)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: < -17°C (< 1°F)

· **Flash point:** < -17°C (< 1°F)

· **Ignition temperature:** 405.0°C (761°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:**

· **Explosion limits:**

Lower:	1.9 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20°C (68°F):** 233.0 hPa (175 mm Hg)

· **Density at 20°C (68°F):** 0.78 g/cm³

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Solvent content:**

Organic solvents:	83.0 %
VOC content:	59.8 %
	490.3 g/l / 4.09 lb/gl

(Contd. on page 6)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 5)

· Solids content: 14.1 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

84-74-2 dibutyl phthalate

Oral	LD50	8000 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
Carcinogenic if inhaled.

12 Ecological information

- **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 7)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 6)

14 Transport information

· DOT regulations:



- Hazard class: 2.1
- Identification number: UN1950
- Packing group: -
- Proper shipping name (technical name): AEROSOLS, flammable
- Label: 2.1

· Land transport ADR/RID (cross-border):



- ADR/RID class: 2 5F Gases
- Danger code (Kemler): 23
- UN-Number: 1950
- Packaging group: -
- Label: 2.1
- Description of goods: 1950 AEROSOLS

· Maritime transport IMDG:



- IMDG Class: 2.1
- UN Number: 1950
- Label: 2.1
- Packaging group: -
- EMS Number: F-D,S-U
- Marine pollutant: No
- Proper shipping name: AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 2.1
- UN/ID Number: 1950
- Label: 2.1
- Packaging group: -
- Proper shipping name: AEROSOLS, flammable

15 Regulations

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

(Contd. on page 8)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 7)

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
78-93-3	butanone
67-63-0	propan-2-ol
1330-20-7	xylene
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
84-74-2	dibutyl phthalate
67-56-1	methanol
	ACRYLIC RESIN
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

68476-86-8	Petroleum gases, liquefied, sweetened
67-64-1	acetone
110-19-0	isobutyl acetate
108-88-3	toluene
141-78-6	ethyl acetate
78-93-3	butanone
14808-60-7	Quartz (SiO ₂)
64742-94-5	Solvent naphtha (petroleum), heavy arom.
123-86-4	n-butyl acetate
13463-67-7	titanium dioxide
67-63-0	propan-2-ol
1330-20-7	xylene
1330-78-5	tris(methylphenyl) phosphate
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)
84-74-2	dibutyl phthalate

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO ₂)
1330-20-7	xylene
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
1333-86-4	Carbon black

· **Chemicals known to cause reproductive toxicity:**

108-88-3	toluene
----------	---------

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	D
108-88-3	toluene	D
78-93-3	butanone	D
1330-20-7	xylene	D
84-74-2	dibutyl phthalate	D
100-41-4	ethylbenzene	D

(Contd. on page 9)

Trade name: 39693 Self Etching Primer Green

(Contd. of page 8)

· IARC (International Agency for Research on Cancer)		
108-88-3	toluene	3
14808-60-7	Quartz (SiO ₂)	1
13463-67-7	titanium dioxide	3
67-63-0	propan-2-ol	3
1330-20-7	xylene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	TRACE AMOUNTS OF 14808-60-7
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B

· NTP (National Toxicology Program)		
14808-60-7	Quartz (SiO ₂)	K

· TLV (Threshold Limit Value established by ACGIH)		
67-64-1	acetone	A4
108-88-3	toluene	A4
14808-60-7	Quartz (SiO ₂)	A2
13463-67-7	titanium dioxide	A4
1330-20-7	xylene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1333-86-4	Carbon black	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)		
14808-60-7	Quartz (SiO ₂)	
13463-67-7	titanium dioxide	
1333-86-4	Carbon black	

· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:

Toxic

Extremely flammable

· Hazard-determining components of labelling:

tris(methylphenyl) phosphate

toluene

dibutyl phthalate

Quartz (SiO₂)

· Risk phrases:

May cause cancer by inhalation.

May cause harm to the unborn child.

Extremely flammable.

Irritating to eyes, respiratory system and skin.

Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

Possible risk of harm to the unborn child.

· Safety phrases:

Avoid exposure - obtain special instructions before use.

(Contd. on page 10)

Printing date 06/24/2005

Reviewed on 09/16/2004

Trade name: 39693 Self Etching Primer Green

(Contd. of page 9)

Keep locked up and out of the reach of children.

Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing and gloves.

In case of insufficient ventilation, wear suitable respiratory equipment.

· Special labeling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

85.8 % by mass of the contents are flammable

Keep out of the reach of children.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: *Environment protection department.*

· Contact: *Mr. George Wallace*

USA