

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2012

Revised On 01/11/2012

1 Identification of the substance and manufacturer

Trade name: BLACK WRINKLE
Product code: 0000162448
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 Phone: 815-895-9101
 www.seymourpaint.com



Emergency telephone number: CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*

2 Composition/information on ingredients

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

74-98-6	propane	18.91%
106-97-8	n-butane	11.11%
67-64-1	Acetone	9.55%
108-88-3	Toluene	9.12%
64742-47-8	Mineral Spirits	8.49%
142-82-5	heptane	7.2%
64742-89-8	VM&P Naphtha	6.0%
108-65-6	PM acetate	1.43%
64742-95-6	Solvent naphtha (petroleum), light aromatic	1.08%
96-29-7	2-butanone oxime	0.17%

3 Hazards identification

Hazard Information for people and the environment:

Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and flame.
 Has narcotizing effect.

Risk phrases: Extremely flammable.
 Irritating to eyes and respiratory system.

Safety phrases: Keep out of the reach of children.
 Keep away from sources of ignition - No smoking.
 Do not breathe gas/fumes/vapour/spray.
 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
 Wear suitable protective clothing and gloves.
 If swallowed, seek medical advice immediately and show this container or label.
 Use only in well-ventilated areas.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

NFPA ratings (0 - 4): Health = 1
 Fire = 4
 Reactivity = 3

HMIS-ratings (0 - 4): Health= 1
 Fire= 4
 Physical Hazard= 3

4 First aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing: Contact physician or poison control center.

5 Firefighting measures

Extinguishing agents: CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.
Special hazards: No further relevant information available.
Protective equipment: No special measures required.

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2012

Revised On 01/11/2012

Trade name: BLACK WRINKLE

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage systems or ground water.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Storage requirements: Observe pressurized container storage regulations. Consult with your local authorities.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

PEL 1800 mg/m³, 1000 ppm
REL 1800 mg/m³, 1000 ppm
TLV Varies mg/m³, 1000 ppm

106-97-8 n-butane

REL 1900 mg/m³, 800 ppm
TLV Varies mg/m³, 1000 ppm

67-64-1 Acetone

PEL 2400 mg/m³, 1000 ppm
REL 590 mg/m³, 250 ppm
TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm
Long-term value: (1188) NIC-475 mg/m³, (500) NIC-200 ppm
BEI

108-88-3 Toluene

PEL Short-term value: C 300; 500* ppm
Long-term value: 200 ppm
*10-min peak per 8-hr shift
REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm
TLV 75 mg/m³, 20 ppm
BEI

142-82-5 heptane

PEL 2000 mg/m³, 500 ppm
REL Short-term value: C 1800* mg/m³, C 440* ppm
Long-term value: 350 mg/m³, 85 ppm
*15-min
TLV Short-term value: 2050 mg/m³, 500 ppm
Long-term value: 1640 mg/m³, 400 ppm

108-65-6 PM acetate

WEEL 50 ppm

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Odor: Aromatic

pH-value: Not determined.

Boiling point: -110°C (-166 °F)

Flash point: -19°C (-2 °F)

Flammability (solid, gaseous): Not applicable.

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol %

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2012

Revised On 01/11/2012

Trade name: BLACK WRINKLE

(Contd. of page 2)

Upper Explosion Limit: 10.9 Vol %
Vapor Pressure: 40 PSI, 2750 hPa
Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)
VOC content: 518.2 g/l / 4.32 lb/gl
VOC content (less exempt solvents): 64.3 %
MIR Value: 1.10
Solids content: 25.8 %
Other information No further relevant information available.

10 Stability and reactivity

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.

13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT Consumer Commodity ORM-D
Class 2.1
Marine pollutant: Yes
Symbol (fish and tree)
EMS Number: F-D,S-U
Packaging Group: --

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

100-41-4 ethyl benzene

98-82-8 isopropylbenzene

California Proposition 65 chemicals know to cause developmental toxicity:

108-88-3 Toluene

EPA:

67-64-1 Acetone

108-88-3 Toluene

142-82-5 heptane

IARC:

108-88-3 Toluene

14807-96-6 Talc (Mg3H2(SiO3)4)

ACGIH:

67-64-1 Acetone

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/11/2012

Revised On 01/11/2012

Trade name: **BLACK WRINKLE**

(Contd. of page 3)

108-88-3	Toluene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
NIOSH:		
1333-86-4	Carbon black	

16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 ISO: International Organization for Standardization
 EPA: Environmental Protection Agency
 IARC: International Agency for the Research of Cancer
 NIOSH: National Institute for Occupational Safety and Health
 TSCA: Toxic Substances Control Act
 CPSC: Consumer Product Safety Commission

USA