

UP0670 LIQUID GOLD PORABLE GLAZING PUTTY

Page 1 Issued: 05/11/2009 Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: UP0670 LIQUID GOLD PORABLE GLAZING PUTTY

Product code: LGOLD/615

Use of substance / preparation: POLYESTER REPAIR PASTE CONTAINING STYRENE

Company name: U-POL US Inc.

630 Selvaggio Drive, Suite 300

Nazareth

PA 18064

USA

Tel: 1-800-340-7824

Fax: 1-800-787-5150

Emergency tel: 1-800-424-9300 (CHEMTREC)

Email: technical@u-pol.com

2. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation. Irritating to eyes and skin.

Other hazards: Flammable. Harmful by inhalation. Irritating to eyes. Irritating to skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: STYRENE 10-30%

EINECS: 202-851-5 CAS: 100-42-5

[-] R10; [Xn] R20; [Xi] R36/38

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.

SAFETY DATA SHEET

UP0670 LIQUID GOLD PORABLE GLAZING PUTTY

Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.		
Ingestion:	Do not induce vomiting. Wash out mouth with water. Consult a doctor.		
Inhalation:	n: Remove casualty from exposure ensuring one's own safety whilst doing so.		
5. FIRE-FIGHTING MEASURES			
Extinguishing media:	Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.		
Exposure hazards:	Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.		
Protection of fire-fighters:	s: Wear protective clothing to prevent contact with skin and eyes.		
6. ACCIDENTAL RELEASE MEASURES			
Personal precautions:	Refer to section 8 of SDS for personal protection details.		
Environmental precautions:	ions: Do not discharge into drains or rivers. Contain the spillage using bunding.		
Clean-up procedures:	Absorb into dry earth or sand.		
7. HANDLING AND STORA	AGE		
Handling requirements:	Ensure there is sufficient ventilation of the area.		
Storage conditions:	Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly		
	closed.		
Suitable packaging:	Must only be kept in original packaging.		
8. EXPOSURE CONTROLS	/ PERSONAL PROTECTION		
Workplace exposure limits			
WEL (8 hr TWA):	100 ppm		
WEL (15 min STEL):	EL (15 min STEL): 250 ppm		
Respirable dust			
WEL (8 hr TWA):	1 mg/m3		
Hazardous ingredients:	STYRENE		
	WEL (8 hr TWA): 430 mg/m3 WEL (15 min STEL): 1080 mg/m3		
Engineering measures:	Ensure there is sufficient ventilation of the area.		
Respiratory protection:	Respiratory protective device with particle filter.		
Hand protection:	Nitrile gloves.		
Eye protection:	Safety glasses with side-shields.		
Skin protection:	Protective clothing.		
9 PHVSICAL AND CHEMI	CAL PROPERTIES		

9. PHYSICAL AND CHEMICAL PROPERTIES

State:	Paste
Colour:	Beige
Odour:	Aromatic
Evaporation rate:	Slow
Solubility in water:	Insoluble

UP0670 LIQUID GOLD PORABLE GLAZING PUTTY

Also soluble in:	Most organic solvents.
Viscosity:	Highly viscous
Viscosity value:	500,000 CP
Flammability limits %: lower:	1.1
upper:	6.1
Flash point°C:	32
Autoflammability°C:	490
Relative density:	1.2
VOC g/l:	222 (1.86 lb/gal)

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.	
Conditions to avoid:	Direct sunlight. Heat. Sources of ignition.	
Materials to avoid:	Oxidising agents.	
Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon m		

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients:	STYRENE
	IVN MUS LD50 90 mg/kg
	ORL MUS LD50 316 mg/kg
	ORL RAT LD50 2650 mg/kg
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.
12. ECOLOGICAL INFORMATION	

Mobility:	Insoluble in water. Heavier than water.
Persistence and degradability:	Not biodegradable.
Bioaccumulative potential:	No data available.
Other adverse effects:	Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D1 Tipping above or underground (e.g. landfill, etc.).

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 3269

Packing group: III Shipping name: POLYESTER RESIN KIT ADR Class: 3

Classification code: F1

UP0670 LIQUID GOLD PORABLE GLAZING PUTTY

Labelling:	3	
	FLAMMABLE LIQUID	
IMDG / IMO		
UN no:	3269 Class: 3	
Packing group:	III EmS: F-E,S-D	
Marine pollutant:		
Labelling:	3	
IATA / ICAO		
UN no:	3269 Class: 3	
Packing group:	III	
Packing instructions:	312	
Labelling:	3	
15. REGULATORY INFORM	IATION	
Hazard symbols:	Harmful.	
Risk phrases:	R20: Harmful by inhalation.	
	R36/38: Irritating to eyes and skin.	
Safety phrases:	S2: Keep out of the reach of children.	
	S3: Keep in a cool place.	
	S46: If swallowed, seek medical advice immediately and show this container or label.	
	S51: Use only in well-ventilated areas.	
Haz. ingredients (label):	STYRENE	
Note:	The regulatory information given above only indicates the principal regulations specifically	
	applicable to the product described in the safety data sheet. The user's attention is drawn to	
	the possible existence of additional provisions which complete these regulations. Refer to all	
	applicable national, international and local regulations or provisions.	
14 OTHED INFORMATION	US VOC CONVERSION FACTOR 250 g/l = 2.1 lb/gal	
16. OTHER INFORMATION		
Other information:	This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.	
	FOR PROFESSIONAL USE ONLY. Read full instructions before use.	

IMPORTANT: This product contains hazardous materials and therefore appropriate personal

Page 4

UP0670 LIQUID GOLD PORABLE GLAZING PUTTY

protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment. Risk phrases used in s.3: R10: Flammable. R20: Harmful by inhalation. R36/38: Irritating to eyes and skin. Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. Addition of reducers, hardeners and other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, this company shall not be held liable for any damage resulting from handling or from contact with the above product. Le informazioni ivi contenute si basano sulle nostre conoscenze alla data sopra riportata. Sono riferite inicamente al prodotto indicato e non costituiscono garanzia di particolari qualita`. L'utilizzatore e` tenuto ad assicurarsi della idoneita` e completezza di tali informazioni in relazione all'utilizzo specifico che ne deve fare. Questa scheda annulla e sostituisce ogni edizione precedente. Addition of reducers, hardeners and other additives over and above Brown Brothers Distribution Limited's recommendations for use, may substantially alter the composition and hazards of the product.