

Air Filtration/Regulation Systems

CAMAIR® CT PLUS™ 5-STAGE FILTER SYSTEM

Complete compressed air treatment and drying center

- Compact and effective—perfect for cramped shop spaces
- Removes dirt, water, humidity and oil from air lines to 0.01 microns—assures superior finishes
- Quick change bowls and air inlet valve accommodate rapid, trouble free maintenance without shutting off main shop air



CAMAIR Filter Systems

Order No.	Description
130522	CT Plus 5-stage compressed air treatment and drying center

DEVILBISS® DAD-500 3-STAGE DESICCANT AIR DRYER SYSTEM

Avoid Costly Redo's

Properly maintained air filtration system eliminates moisture and dirt in air lines



Desiccant Air Dryer

Order No.	Model No.	Description
130026	DAD-500	3-stage desiccant air dryer system

Air Filtration Service Parts from DeVilbiss® Automotive Refinishing

Air Filtration Unit	Order No.	Service Part Description	Replacement Interval
 Camair® CT-30	130504	 3-stages in one! Quick change bag removes water vapor from compressed air down to a dew point of -40°F. Desiccant Cartridge for CT30.	Indicator provided green=OK yellow=replace
 Camair® 130523	130517	 First stage removes water and dirt to 5 microns. Filter element, water and particulates for the new Camair 2-stage.	Replace every 3 months
	130518	 Second stage removes oil and vapors to .01 microns. Filter element, coalescing for the new Camair 2-stage.	 with air flowing
 Camair® 130526	130517	 First stage removes water and dirt to 5 microns. Filter element, water and particulates for the new Camair 3-stage with 2 self-relieving regulators.	Replace every 3 months
	130518	 Second stage removes oil and vapors to .01 microns. Filter element, coalescing for the new Camair 3-stage with 2 self-relieving regulators.	 with air flowing
	130527	 Third stage removes oil vapor and odors. Filter element, charcoal for the new Camair 3-stage with 2 self-relieving regulators.	Replace every 6 weeks
 DeVilbiss® DAD-500	HAF-6	 First stage removes water and dirt to 5 microns. Filter element, water and particulates for DAD-500.	Replace every 3 months
	HAF-28	 Second stage removes oil and vapors to .01 microns. Filter element, coalescing for DAD-500.	Indicator provided green=OK red=replace (check with air flowing)
	DAD-1	 Third stage removes humidity from the air. 10 lbs Desiccant refill for DAD-500.	Indicator provided blue=OK pink/white=replace
	DAD-600-1	 Complete Tune Up Kit for DAD-500. 10 lbs desiccant, filter element, coalescing filter element	See above for filter change outs
 Camair® TS-10	130507	 Second stage removes oil and vapors to .01 microns. Filter element, coalescing for TS-10.	Replace every 3 months
	130508	 Complete Tune Up Kit for TS-10. 10 lbs desiccant, coalescing filter, humidity indicator.	Indicator provided green=OK yellow=replace
 Sharpe® 6760	130517	 First stage removes water and dirt to 5 microns. Filter element, water and particulates for Sharpe 6760. Replaces Sharpe 22645.	Replace every 3 months
	130507	 Second stage removes oil and vapors to .01 microns. Filter element, coalescing for Sharpe 6760. Replaces Sharpe 22655.	 with air flowing
	DAD-1	 Third stage removes humidity from the air. 10 lbs Desiccant refill for two 5-lbs changes of Sharpe 6760. Replaces Sharpe 6765-1.	Indicator provided blue=OK pink/white=replace (place indicator paper into sight glass)
 FinishLine® HAR-602	HAF-39	 Removes water and dirt to 5 microns. Filter element, water and particulates for HAR-602.	Replace every 3 months
 Sharpe® F88	130528	 Removes water and dirt to 5 microns. Filter element, water and particulates for Sharpe F88. Replaces Sharpe 32719.	Replace every 3 months
 Sharpe® 606	HAF-39	 Removes water and dirt to 5 microns. Filter element, water and particulates for Sharpe 606. Replaces Sharpe 19930.	Replace every 3 months

Camair, DeVilbiss, and FinishLine are registered trademarks of Illinois Tool Works, Inc. Sharpe is a registered trademark of Graco Inc. and not affiliated with Illinois Tool Works, Inc.