

PRODUCT FEATURES & APPLICATION



Touch Dry 2 hrs

Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

PRIMERLESS URETHANE

Stock Number CUS, Part Number # 9006

Size: 300ML (11Oz.) Cartridge

Description:

Primerless Urethane is a user friendly, fast setting autoglass urethane that provides excellent strength (MVSS 212 & 216) because of its powerful adhesion to glass and metal. Can also be used as a high strength single component adhesives for re-applying moldings and ground effects.

Features:

- Primerless Urethane.
- Powerful adhesion to glass and metal.
- Passes US MVSS 212 and 216 drive away tests.

Provides the much needed strength once cured.

Surface Preparation:

1. Surfaces must be clean and dry in order to insure a water tight seal.
2. Clean surface with some fast drying solvent.(Sure Solv Part # BSS)
3. Dry surface with heat gun, heat lamp or air.

Application Instructions:

1. Install cartridge in chalking gun.
2. Cut tip of cartridge to desired size
3. Puncture hole through tip to extrude primerless urethane.
4. Gently squeeze gun to extrude some product out of cartridge.
5. Apply product to the pinchweld area.
6. Clean any excessive material promptly. Caution must be taken with solvents on some types of plastics and painted surfaces.
7. Install Windshield
8. Drive away time is 2 to 3 hours

NOTE: Do not use excessive pressure. The cartridge will blow back material at back side.

Touch Dry 2 Hours

Full Cure 24 Hours

Note: Avoid applying any materials on or near catalytic converters, mufflers due to extreme heat.

In the event the MSDS (Material Safety Data Sheet) on this product is not in your files, you can request one from Dominion Sure Seal Regulatory Compliance at 1800 265-0790, ext. MSDS.

Call 1-800-265-0790 or visit us on the web www.dominionsureseal.com