

5 STAR ADVANTAGE® AUTOBODY PRODUCTS

TECHNICAL DATA INFORMATION

DATED: MAY 2020

PRODUCT NUMBER DESCRIPTION

#3311 Paintable Rubberized Undercoating Aerosol (Black) 18 fl. oz 12/cs

DESCRIPTION:

#3311 is a paintable undercoating for all vehicle undercarriages. Forms a rubberized skin that reduces road noise and protects metal from salt corrosion and road debris. Dries fast and does not sag. Does not 'bleedthru' when topcoated.

SUGGESTED USES:

Panel & fender undersides	Hoods & decks
Trunk interiors	Section repairs
Weld joints	Rust holes
All chassis parts	

DIRECTIONS:

1. Surface must be clean and dry before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10 °C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm).
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can right side up and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

Dry Time*:

To touch 10 minutes

To handle 6 hours

*At 72° F, 50% humidity, 1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: Low Lustre, 15-25

*AS MEASURED ON A 60° GLOSS METER

PROPERTIES:

Flammability	“Extremely Flammable”
Flash point	-40 F
Specific Gravity	0.80
Solids Content	~60%
VOC content	~39%, cannot exceed 40%
MIR value	~0.99
HAPs content	18%
Storage Temperature	40-90°F
Application Temperature	50-100°F
Durability	Very Good
Abrasion Resistance	Very Good
Heat Resistance	3000° F
Gasoline Resistance	No
Resin System	Petroleum Asphalt
Shelf life	Guaranteed for 2 years

SAFETY INFORMATION - FOR INDUSTRY USE ONLY

DANGER Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN.

WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov.

AVERTISSEMENT: Cancer et Harm Reproductive

www.P65Warnings.ca.gov

ADVERTENCIA: Cáncer y Daños Reproductivos

www.P65Warnings.ca.gov

For Chemical Emergencies/Pour les urgences chimiques

Para Emergencias Químicas

Contact CHEMTREC (day or night) at 1-800-424-9300

www.5starxtreme.com / www.advantagerefinish.com

Manufactured in U.S.A (Manufactured for - ABI/Autobody Brands International a division of IAMG/International Autobody Marketing Group)
1505 N. Hayden Rd. Ste. 111, Scottsdale, AZ 85257
1-87-REFINISH

Distributed in Canada by: ABI (Autobody Brands International)
A division of IAMG/International Autobody Marketing Group
1368 United Blvd., Unit 102, Coquitlam, BC V3K 6Y2, Canada