



BLACK WRINKLE FINISH

#16-2448

A durable and long lasting finish which has a unique wrinkled texture. To achieve the desired wrinkling effect, **two coats** are needed. The second coat must be applied approximately three minutes after the first coat. The two coats are required to provide adequate film thickness for "wrinkling". The "wrinkling" effect does not appear immediately after spraying. A minimum of eight hours of drying is required.

Suggested Uses:

Home and office equipment
Marine and automobile use
Instruments and tool boxes

Benefits:

Excellent hiding qualities
Hides surface imperfections
Resists oil, gas, grease
Can be used where harsh
Conditions break down conventional coatings.

Packaging:

UPC Code	043281001281
Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	Consumer Commodity ORM-D, UN 1950
Hazard Class	2.1

Properties:

Flammability	"Extremely Flammable"
Flash point	-4F
Specific Gravity	0.80
Solids Content	~26%
VOC content	~64%, cannot exceed 60%
MIR value	~1.10, cannot exceed 1.20
HAPs content	6%
Storage Temperature	40-90F
Application Temperature	50-100F
Durability	Very Good
Abrasion Resistance	Very Good
Heat Resistance	250° F
Gasoline Resistance	Yes
Resin System	Vinyl
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch 30 minutes

8 hours is required to complete the wrinkling process

*At 72° F, 50% humidity,
1.5 mil thickness

Curing/Recoat time is extended with multiple coats and excessively thick coats

Gloss*: Varies with pattern

*as measured on a 60° gloss meter

Available Colors:

Part #	Description	UPC Code
--------	-------------	----------