



DOLPHIN GLAZE

Brushable/Pourable Polyester Putty

Description

DOLPHIN GLAZE is a two component chemical liquid used for the final skimming of a polyester body putty repair or for direct application onto minor imperfections on bodywork prior to over painting. **DOLPHIN GLAZE** is designed for the professional user and combines excellent leveling properties together with easy sanding.

Health and Safety Statement

FOR PROFESSIONAL USE ONLY. Read full instructions before use. IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at WWW.U-POL.COM. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

Surface preparation and instructions for use

DOLPHIN GLAZE polyester putty can be used on the many common surfaces:-

- Bare steel - degrease and sand with 80 grit paper.
- Galvanized and other Zinc coated steels - degrease and sand with 120 grit paper.
- Aluminum - degrease and sand with 120 grit paper
do not apply over etch primer.
- Fully cured paint surfaces - degrease and sand with 180 grit paper.

Mixing ratio

100% by weight **DOLPHIN GLAZE** polyester putty

2% by weight U-POL hardener for polyester putty

The exact mixing ratio is not critical although over or under catalyzation may affect the gel time.

U-POL Dolphin Glaze is a thick liquid and should be mixed in small quantities on a flat non-porous surface. To obtain optimum results apply the mixed liquid in small quantities to form a thin film - during cure surface imperfections will flow out to leave a level repair which requires only a small amount of sanding.

Pot life

Once mixed, 4 min. 30 sec. at 70°F with 2% hardener.

Tools

Mixing board, filler knife, plastic or rubber spreader.

Drying time

Sandable after 20 min. at 70°F.

Over- painting

DOLPHIN GLAZE polyester putty can be over-painted with most paint systems.

Product codes

UP713 - 30 fl.oz can.

UP714 - 15 fl. oz plastic bag.

U-POL US, Inc., 630 Selvaggio Dr, Suite 300, Nazareth, PA 18064

Tel: (800) 340 7824; Fax: (800) 787 5150

Email: sales-us@u-pol.com Website: www.u-pol.com