Printing date 10/12/2015

1 Identification

- · Product identifier
- · Trade name: 780-04 Showcar Black Basecoat
- · Article number: 780-04
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Manufactured for: IAMG International Autobody Marketing Group, 1505 North Hayden Road, Ste.111, Scottsdale, AZ 85257 Information phone: 480.451.4451
- · Information department: 1-87-REFINISH
- · Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s)	identificat	ion
· Classificatio	on of the sub	stance or mixture
J.		
<u>₹</u> 3	GHS02 Flan	ne
Flam. Liq. 2	H225	Highly flammable liquid and vapor.
	GHS08 Hea	Ith hazard
	Grieborrea	
Carc. 2	H351	Suspected of causing cancer.
Repr. 1B	H360	May damage fertility or the unborn child.
$\langle ! \rangle$	GHS07	
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
· Label eleme · GHS label e		

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



Reviewed on 10/12/2015

(Contd. on page 2) USA

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Reviewed on 10/12/2015

(Contd. of page 1)

- · Signal word Danger
- · Hazard-determining components of labeling: Carbon black acetone

benzyl butyl phthalate

4-chloro-alpha, alpha, alpha-trifluorotoluene

· Hazard statements

- H225 Highly flammable liquid and vapor.
- Causes skin irritation. H315
- H319 Causes serious eye irritation.
- May cause an allergic skin reaction. H317
- H351 Suspected of causing cancer.
- H360 May damage fertility or the unborn child.
- H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Precautionary s	tatements
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves / eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P303+P361+P35	3 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+P351+P33	8 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, it present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
DEAA	Dispass of contents (container in considered with level/vertices)// ational/internations

- Dispose of contents/container in accordance with local/regional/national/international P501 regulations.
- · Classification system:
- NFPA ratings (scale 0 4)



· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3) USA

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

(Contd. of page 2)

· vPvB: Not applicable.

*

3 Composition/information on ingredients		
 Chemical characterization: Mixtures Description: Mixture: consisting of the following components. Weight percentages 		
· Dangerous components:		
67-64-1 acetone	13 - 30%	
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene	13 - 30%	
110-43-0 heptan-2-one	10 -13%	
1333-86-4 Carbon black	7 - 10%	
85-68-7 benzyl butyl phthalate	1.5 - 5%	
41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate	<u><</u> 1%	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4) USA

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Reviewed on 10/12/2015

(Contd. of page 3)

• Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

· Handling:

- Precautions for safe handling
 No special measures required.
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

67-64-1 acetone

- PEL Long-term value: 2400 mg/m³, 1000 ppm
- REL Long-term value: 590 mg/m³, 250 ppm
- TLV Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm BEI

110-43-0 heptan-2-one

- PEL Long-term value: 465 mg/m³, 100 ppm
- REL Long-term value: 465 mg/m³, 100 ppm
- TLV Long-term value: 233 mg/m³, 50 ppm

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Page 5/11

Reviewed on 10/12/2015

(Contd. of page 4)

- REL Long-term value: 3.5* mg/m³ *0.1 in presence of PAHs;See Pocket Guide Apps.A+C
- TLV Long-term value: 3* mg/m³ *inhalable fraction
- Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately.

Avoid contact with the eyes and skin. · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of guality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6) USA

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Reviewed on 10/12/2015

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

 Information on basic physical and ch General Information Appearance: Form: Color: Odor: Odour threshold: 	nemical properties Liquid According to product specification Characteristic Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 55 °C
· Flash point:	-18 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	465 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
 Explosion limits: Lower: Upper: 	1.0 Vol % 13.0 Vol %
· Vapor pressure at 20 °C:	233 hPa
 Density at 20 °C: Relative density Vapour density Evaporation rate 	1.0604 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water): Not determined.
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.
 Solvent content: Organic solvents: 	66.9 %

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Reviewed on 10/12/2015

(Contd. of page 6)

VOC content:	16.8 % 382.7 g/l / 3.19 lb/gl
Solids content:	33.1 %
• Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Irritant
- Carcinogenic categories
- · IARC (International Agency for Research on Cancer)
- 1333-86-4 Carbon black

85-68-7 benzyl butyl phthalate

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

2B

3

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Reviewed on 10/12/2015

(Contd. of page 7)

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

UN1263

Paint

PAINT

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA
- · UN proper shipping name
- · DOT
- · ADR
- · IMDG, IATA
- · Transport hazard class(es)
- · DOT



- · Class
- · Label
- · ADR, IMDG, IATA



3 Flammable liquids 3

3 Flammable liquids

3

II

1263 Paint, special provision 640D

- · Class
- · Label
- · Packing group
- · DOT, ADR, IMDG, IATA
- · Environmental hazards:
- · Marine pollutant:
- · Special precautions for user

No Warning: Flammable liquids

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Reviewed on 10/12/2015

(Contd. of page 8)

· EMS Number:	<i>F-E,<u>S-E</u></i>
 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	of Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· ADR · Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

- \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara
- Section 355 (extremely hazardous substances): None of the ingredient is listed.
- Section 313 (Specific toxic chemical listings): None of the ingredients is listed.
- TSCA (Toxic Substances Control Act):
 - 67-64-1 acetone
 - 98-56-6 4-chloro-alpha, alpha, alpha-trifluorotoluene
 - 110-43-0 heptan-2-one
 - 9004-36-8 Cellulose Acetate Butyrate
 - 1333-86-4 Carbon black
 - 763-69-9 ethyl 3-ethoxypropionate
 - 85-68-7 benzyl butyl phthalate
- 41556-26-7 bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate
- 82919-37-7 Methyl (1,2,2,6,6,- pentamethyl-4-piperidinyl) sebacate
- 106-79-6 Dimethyl sebacate(Impurity)
- 2403-89-6 4-Piperidinol, 1,2,2,6,6 pentamethyl- (Impurity)
- · Proposition 65
- · Chemicals known to cause cancer:
- 1333-86-4 Carbon black
- Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Reviewed on 10/12/2015

	(Contd. of page 9)
 Chemicals known to cause reproductive toxicity for males: 	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
85-68-7 benzyl butyl phthalate	
· Cancerogenity categories	
· EPA (Environmental Protection Agency)	
67-64-1 acetone	1
85-68-7 benzyl butyl phthalate	С
· TLV (Threshold Limit Value established by ACGIH)	
67-64-1 acetone	A4
1333-86-4 Carbon black	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)	

- 1333-86-4 Carbon black
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

Carbon black

acetone

benzyl butyl phthalate

4-chloro-alpha,alpha,alpha-trifluorotoluene

Hazard statements

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H360 May damage fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

- Keep away from heat/sparks/open flames/hot surfaces. No smoking. P210
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P280 Wear protective gloves / eye protection / face protection.
- Ground/bond container and receiving equipment. P240
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P321 Specific treatment (see on this label).
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 11) USA

Printing date 10/12/2015

Trade name: 780-04 Showcar Black Basecoat

Reviewed on 10/12/2015

(Contd. of page 10)

P312	Call a POISON CENTER/doctor if you feel unwell.
P363	Wash contaminated clothing before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: 1-480-451-4451
- · Date of preparation / last revision 10/12/2015 / 10
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord european sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 2: Carcinogenicity, Hazard Category 2

Repr. 1B: Reproductive toxicity, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

* Data compared to the previous version altered.

USA