# SAFETY DATA SHEET

# Prepared according to USA OSHA Hazcom 2012 / Canada WHMIS 2015



**Date Prepared:** 11/12/2015

MSDS No: BCYH Part B Color Your Hippo ENG

# **BCYH Part B COLOR YOUR HIPPO Tintable Bedliner & Protective Coating**

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: BCYH Part B COLOR YOUR HIPPO Tintable Bedliner & Protective Coating

**Product Description:** Part B Truck Bed Liner Coating, 680 ml / 23 fl oz US **General Use**: Truck Bed Liner Coating - Vehicle Refinishing Product

**Product Stock/Code:** BCYH / 100600 (Kit: 1.7 L / 1.8 qt) **Chemical Family**: Solvent-based / À base de solvant

**Molecular Formula**: Mixture / Mélange

## Manufacturer / Supplier

Dominion Sure Seal Ltd. 6175 Danville Road, Mississauga Ontario, Canada L5T 2H7

Fax: 905-670-5174

www. dominion sureseal. com

**Customer Service:** 905-670-5411

# **Emergency Telephone Numbers (24 hour)**

CANUTEC : (613) 996-6666 CHEMTREC : (800) 424-9300

## 2. HAZARDS IDENTIFICATION

#### **GHS CLASSIFICATIONS**

#### **Health:**

Eye Irritation, Category 2 Skin Irritation, Category 2 Specific Target Organ Toxicity - Single Exposure, Category 3 (Narcotic Effects) Specific Target Organ Toxicity - Repeated Exposure, Category 2

Carcinogenicity, Category 2

## Physical:

Flammable Liquids, Category 2

#### **GHS LABEL**

Hazardous components for labelling:

p-Chlorobenzotrifluoride, n-Butyl acetate, Propylene glycol methyl ether acetate and Ethylbenzene



Flame



Exclamation mark



Health hazard

SIGNAL WORD: DANGER HAZARD STATEMENTS

- H225: Highly flammable liquid and vapour.
- H319: Causes serious eye irritation.
- H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness.
- H373: May cause damage to organs (hearing organs and central nervous system) through prolonged or repeated exposure.
- H351: Suspected of causing cancer.

## PRECAUTIONARY STATEMENT(S)

#### **Prevention:**

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P240: Ground and bond container and receiving equipment.
- P241: Use explosion-proof electrical / ventilating / lighting equipment.
- P242: Use non-sparking tools.
- P243: Take action to prevent static discharges.
- P264: Wash hands thoroughly after handling.
- P260: Do not breathe mist, vapours or spray.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves and eye protection.

## Response:

- P308+P313: IF exposed or concerned: Get medical advice/ attention.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313: If eye irritation persists: Get medical advice/attention.
- P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P332+P313: If skin irritation occurs: Get medical advice/attention.
- P362+P364: Take off contaminated clothing and wash it before reuse.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P314: Get medical advice/attention if you feel unwell.
- P370+P378: In case of fire: Use dry chemical or foam to extinguish.

## Storage:

- P403+P235: Store in a well-ventilated place. Keep cool.
- P405: Store locked up.
- P233: Keep container tightly closed.

#### Disposal:

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

## **Emergency Overview**

#### **Immediate Concerns:**

Flammable liquid and vapor. Causes serious eye irritation. Moderately irritating to the skin. Vapours may cause drowsiness and dizziness. Suspected of causing cancer. Overexposure may cause nerve damage.

## **Hazards Not Otherwise Classified:**

No data available.

#### **Comments:**

- < 5 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity.
- See sections 9 and 10 for more detailed information on physicochemical effects.
- See section 11 for more detailed information on health effects.
- See sections 12 for more detailed information on environmental effects.

This product is a consumer product and is labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations which take precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling. The actual container label will not include the above label elements. The labeling above applies to products used solely for industrial / professional use.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS No.
p-Chlorobenzotrifluoride	27 - 30	98-56-6
n-Butyl acetate	14 - 16	123-86-4
Propylene glycol methyl ether acetate	2.5 - 3.5	108-65-6
Ethylbenzene	1 - 2	100-41-4
Stoddard Solvent	0.5 - 1	8052-41-3

**Comments:** There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

#### 4. FIRST AID MEASURES

## **Eye Contact:**

In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention, if irritation persists.

#### Skin Contact:

Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

## Ingestion:

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

## **Inhalation:**

If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain medical attention if breathing difficulty persists.

#### Signs and Symptoms of Overexposure

#### **Eve Contact:**

Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

#### **Skin Contact:**

Contact causes skin irritation. Cured material is difficult to remove. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

#### **Ingestion:**

Substance may be harmful if swallowed. May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

#### Inhalation:

High vapor or spray mist concentrations may be harmful if inhaled. May cause headaches and dizziness. High vapor concentrations may cause drowsiness.

## Notes to Physician:

Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

#### **Additional Information:**

Not Available

#### 5. FIRE FIGHTING MEASURES

# Flammable Properties:

Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flash point. Product can be ignited by static discharge.

## **Extinguishing Media:**

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

#### **Hazardous Combustion Products:**

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

## Fire Fighting Procedures:

Containers can build up pressure if exposed to heat (fire).

## Fire Fighting Equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

## Sensitivity to Static Discharge:

Product is sensitive to static discharge.

## Sensitivity to Mechanical Impact:

Product is not sensitive to mechanical impact.

#### 6. ACCIDENTAL RELEASE MEASURES

## **Small Spill:**

Eliminate all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

# **Environmental Precautions**

#### Water Spill:

Do not discharge into drains/surface waters/groundwater.

# Land Spill:

Avoid runoff into storm sewers and ditches which lead to waterways.

## **Special Protective Equipment:**

Clean up spills immediately, observing precautions in Protective Equipment section 8.

## 7. HANDLING AND STORAGE

## **General Procedures:**

Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids. Ensure thorough ventilation of stores and work areas.

#### Handling:

Do not use in the presence of open flame or spark. Use only in a well ventilated area. Wear recommended personal protective equipment. Keep container closed when not in use. Avoid breathing vapours or mist. Avoid contact with eyes, skin, and clothing. After handling, always wash hands thoroughly with soap and water.

#### Storage:

Store away from heat, sparks, open flames, strong oxidizing agents and direct sunlight. Protect from physical damage. Keep container tightly closed and in a well-ventilated place. Store in a cool place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Exposure Guidelines** 

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		Occupational Exposure Limits					
		OSHA PEL ACGIH TLV NIOSH F		OSHA PEL		H REL	
Chemical Name		ppm	mg/m³	ppm	mg/m³	ppm	mg/m³
p-Chlorobenzotrifluoride	TWA	[1]	[1]	[1]	[1]	[1]	[1]
Drawylana alyeal mathyl athar acatata	TWA	[1]	[1]	[1]	[1]	50 [2]	275 [2]
Propylene glycol methyl ether acetate	STEL	[1]	[1]	[1]	[1]	100 [2]	550 [2]
[February 2000]	TWA	100	435	20		100	435
Ethylbenzene	STEL	[1]	[1]	[1]	[1]	125	545
Stoddard Solvent	TWA	500	2900	100	572	[1]	[1]

## Footnotes:

- 1. NL: This material does not have established exposure limits.
- 2. European Union

## **Engineering Controls:**

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Avoid breathing mists; if general ventilation or local exhaust is inadequate, persons exposed to mists should wear approved breathing devices. Use explosion-proof ventilation equipment.

## **Personal Protective Equipment**

## **Eyes and Face:**

Wear safety glasses with side shields (or goggles). Contact lenses should not be worn when working with this product. Eye wash fountains should be readily available to areas of use and handling.

#### **Skin Contact:**

Wear chemical resistant gloves.

## Respiratory:

If engineering controls do not maintain airborne concentrations below recommended exposure limits, an approved respirator must be worn. Respirator type: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

## **Protective Clothing:**

Wear protective clothing as necessary to prevent contact.

#### **Work Hygienic Practices:**

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled dothing/wash thoroughly before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State : Liquid

Odor : Aromatic

Odor Threshold : Not Available

**Appearance**: Thixotropic liquid

**Color** : Opaque, Translucent

pH : No data available.

**% Volatiles** : 49 % w/w

**Flash Point and Method**: 18 to 23°C Closed Cup (n-Butyl acetate; Ethylbenzene)

Flammable Limits : 1.0 to 7.6

**Notes:** Based on data for n-butyl acetate; ethylbenzene.

**Autoignition Temperature**: No data available.

**Vapor Pressure** : 1.3 kPa [n-Butyl acetate] at 20°C

Vapor Density : > 1

**Boiling Point** : 126°C (n-Butyl acetate)

Freezing Point : Not Available

Melting Point : Not Available

**Solubility in Water**: Practically insoluble

**Evaporation Rate** 

(n-butyl acetate = 1) :> 1

**Density** : 1.17±0.01g/ml at 20°C

**Viscosity** : 15000 to 30000 cps at 25°C

**VOC Content** : 315 g/l (2.63 lb/gal), less exempt solvents

Oxidizing Properties : None

**Comments:** 

# **VOC Compliance Statement - BCYH, Part B**

Part B VOC Content: Less Exempts: 315 g/l (2.63 lb/gal)

Total Material: 236 g/l (1.97 lb/gal)

Part B Density: 1.17 g/ml Part B Total Volatiles: 48.6 % w/w

Part B Exempt Content:28.4 % w/w; 24.8% v/v (PCBTF)Mixed Kit VOC ContentLess Exempts: 255 g/l (2.1 lb/gal)No tint added:Total Material: 190 g/l (1.60 lb/gal)

**VOC Regulation:** VOC Concentration Limits for Automotive Refinishing Products

Regulations – Canada

**Coating Category:** Truck Bed Liner Coating

The ready to apply kit VOC content meets the 310 g/l (2.59 lb/gal) limit for Truck Bed

Liner Coatings.

Canada compliant. Do not thin with solvents

**VOC Regulation:** SMAQMD Rule 459 – Automotive, Mobile Equipment and Associated

Parts and Components Coating Operations – Sacramento Metropolitan

AQMD, California

**Coating Category:** Truck Bed Liner Coating

The ready to apply kit VOC content does not meet the 200 g/l (1.67 lb/gal) limit for Truck Bed Liner Coatings. Not for sale in Sacramento Metropolitan AQMD. May be sold in the rest of California. Do not thin with solvents.

## 10. STABILITY AND REACTIVITY

**Reactive Hazard**: No

## **Hazardous Polymerization:**

Not expected to occur.

## Stability:

Stable.

#### Conditions to Avoid:

Keep away from flames and any object that sparks.

# **Possibility of Hazardous Reactions:**

Not available.

# **Hazardous Decomposition Products:**

Carbon Monoxide and other toxic vapors.

## **Incompatible Materials:**

Oxidizing materials.

## 11. TOXICOLOGICAL INFORMATION

## **Product Acute Toxicity**

Chemical Name	ORAL LD <sub>50</sub> mg/kg(rat)	DERMAL LD <sub>50</sub> mg/kg(rabbit)	INHALATION LC <sub>50</sub> mg/l
p-Chlorobenzot rifluoride	> 6700 13,000 11,500	> 2000	33.0(rat;4h) 22.0(rat;4h) 20.0(mouse)
n-Butyl acetate	13,100(rat) 11,000(rat)	>14,400	>45.0(rat;4h)
Propylene glycol methyl ether acetate	>10,000 8532 13,700	>5000(rat) >19,400(rbt)	10.8(rat;3h) 23.5(rat;6h) (no deaths)
Ethylbenzene	5460 3500 5627(mouse)	17,800 15,354	17.2(rat;4h) 13,367 ppm (rat;2h)
Stoddard Solvent	> 5000	> 3000	8.5(rat;8h) >5.5(rat;4h)

**Acute Toxicity - Dermal LD**<sub>50</sub>: The calculated ATE is >2000 mg/kg.

#### Notes:

Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture.

**Acute Toxicity - Oral LD**<sub>50</sub>: The calculated ATE is >2000 mg/kg.

#### Notes:

Based on available data, the classification criteria for Acute Oral Toxicity are not met for this mixture.

**Acute Toxicity - Inhalation LC<sub>50</sub>:** The calculated ATE is >20 mg/l/4h (vapours) and >5 mg/l/4h (mists).

#### Notes:

Based on available ingredient data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture. High vapor concentrations may be harmful if inhaled. Excessive vapor concentrations are attainable. Saturated vapors can be encountered in confined spaces and/or under conditions of poor ventilation.

## Toxicological Data:

< 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

No additional toxicology information is available for this product itself. (See Component Toxicity Information).

# **Primary Routes of Entry:**

Eye contact. Inhalation. Skin contact. Ingestion.

# **Eye Irritation / Serious Eye Damage:**

Contains: p-Chlorobenzotrifluoride. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

#### Skin Irritation / Corrosion:

Contains: p-Chlorobenzotrifluoride. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as skin irritant, category 2). Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

## Carcinogenicity

Chemical Name	NTP Status	IARC Status	OSHA Status	Other
p-Chlorobenzotrifluoride				
n-Butyl acetate				
Propylene glycol methyl ether acetate				
Ethylbenzene		2B		A3 (ACGIH)
Stoddard Solvent				

## Notes:

Contains: Ethylbenzene. Ethylbenzene has been classified as being possibly carcinogenic to humans (Group 2B). The mixture is classified as: Carcinogenicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ( $\geq 0.1\%$  ingredients classified as a Carcinogen, category 2).

#### **Specific Target Organ Toxicity - Repeated Exposure:**

The mixture is classified as: Specific Target Organ Toxicity - Repeated Exposure, category 2, based on ingredient data using the applicable cut-off/concentration limits ( $\geq 1.0\%$  ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2). Prolonged inhalation may be harmful. Chronic exposure to organic solvents such as Xylene and Ethylbenzene have been associated with various neurotoxic effects including permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability, and loss of coordination. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

## Respiratory / Skin Sensitizer.:

Based on available data, the classification criteria for skin/respiratory sensitization are not met for this mixture  $(< 0.1\% \text{ ingredients classified as a skin sensitizer, category 1 or sub-category 1A and } < 1.0\% \text{ ingredients classified as a skin/respiratory sensitizer, sub-category 1B}).}$ 

#### Reproductive Toxicity:

Based on available data, the classification criteria for Reproductive Toxicity are not met for this mixture (< 0.1%

ingredients classified as Reproductive Toxicity, category 1 or 2).

## **Specific Target Organ Toxicity - Single Exposure:**

Contains: p-Chlorobenzotrifluoride. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits (≥ 20% summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3). Can cause central nervous system depression (including unconsciousness). High vapor concentrations may cause drowsiness. May cause headaches and dizziness.

## Germ Cell Mutagenicity:

Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

# **Aspiration Hazard:**

Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture (< 10% ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity > 20.5 mm<sup>2</sup>/s at 40 °C).

#### 12. ECOLOGICAL INFORMATION

#### **Environmental Data:**

No data available.

## **Ecotoxicological Information:**

No data available.

#### **Bioaccumulation/Accumulation:**

No data available.

# **Distribution:**

No data available.

## Aquatic Toxicity (Acute):

No data available.

#### **Chemical Fate Information:**

No data available.

#### 13. DISPOSAL CONSIDERATIONS

# **Disposal Method:**

Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

## **Product Disposal:**

Empty containers retain product residue; observe all precautions for product. Decontaminate containers prior to disposal.

## 14. TRANSPORT INFORMATION

#### **DOT (Department of Transportation)**

Proper Shipping Name : Paint

**Primary Hazard Class/Division:** 3

UN/NA Number : 1263

Packing Group : II

# Other Shipping Information:

With an inner packaging < 5.0 L, this product may be shipped as a Limited Quantity.

## Air (ICAO/IATA)

Shipping Name : Paint UN/NA Number : 1263

**Primary Hazard Class/Division:** 3

Packing Group : II

Subsidiary Risk : None

**Label** : Flammable Liquid

Vessel (IMO/IMDG)

Shipping Name : Paint UN/NA Number : 1263

**Primary Hazard Class/Division:** 3

Packing Group : II

Marine Pollutant : None

**Note:** With an inner packaging < 5.0 L, this product may be shipped as a Limited Quantity.

## Canadian Transportation of Dangerous Goods Regulations

Shipping Name : Paint UN/NA Number : 1263

Primary Hazard Class/Division: 3

Packing Group : II

#### **TDG Note:**

With an inner packaging < 5.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

#### 15. REGULATORY INFORMATION

#### **UNITED STATES**

## SARA Section 311/312 Hazard Categories

Fire Hazard : Yes
Sudden Release of Pressure : No
Reactive Hazard : No
Product Acute Toxicity : Yes
Product Chronic Toxicity : Yes

#### **EPCRA Section 313 Toxic Chemicals**

Chemical Name	Wt.%	CAS No.
Ethylbenzene	1 - 2	100-41-4

## **EPCRA Section 302 Extremely Hazardous Substances**

## **EPCRA Status:**

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

## **CERCLA Hazardous Substances and Reportable Quantities (RQ)**

Chemical Name	Wt.%	RQ
n-Butyl acetate	14 - 16	5,000
Ethylbenzene	1 - 2	1,000

# TSCA (The Toxic Substances Control Act)

#### **TSCA Status:**

All components are included or are otherwise exempt from inclusion on this inventory.

## CAA 112(b) - Hazardous Air Pollutants

Chemical Name	Wt.%	CAS No.
Ethylbenzene	1 - 2	100-41-4

## CAA 112(r) - List of Substances for Accidental Release Prevention:

This product contains no chemicals subject to CAA 112(r).

## **California Proposition 65**

Chemical Name	Wt.%	Listed
Ethylbenzene	1 - 2	Cancer

## OSHA Hazard Communication Standard (29 CFR 1910.1200):

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

#### **CANADA**

## WHMIS Hazard Symbol and Classification

See Section 2 for details.

#### WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

#### WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

# **CEPA - National Pollutant Release Inventory (NPRI):**

Name	CAS No.	NPRI Part No.
Ethylbenzene	100-41-4	1A, 5 (VOC)
2-Methoxy-1-methylethylacetate	108-65-6	5 (VOC)

## Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

#### Comments

VOC Content -- See section 9.

#### 16. OTHER INFORMATION


Reason for Issue: NEW

**Approved By:** Jim Gordon **Title:** R&D Chemist / Chemiste de R&D

Prepared By: Regulatory Compliance / Conformité réglementaire Date Prepared: 11/12/2015

**Information Contact:** 905-670-5411

# HEALTH \* 2 FLAMMABILITY 3 PHYSICAL HAZARD 0



NFPA 30 / 30B Storage Classification: Flammable Liquid IB

G

## **Manufacturer Supplemental Notes:**

None

#### **Data Sources:**

Not Available

#### Additional MSDS Information:

PERSONAL PROTECTION

N/AV Not Available

N/AP Not Applicable

ND Not yet determined

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer

MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Act

SARA The Superfund Amendments and Reauthorization Act

WHMIS Workplace Hazardous Materials Information System

#### **General Statements:**

None

#### Comments:

None

# Manufacturer Disclaimer:

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.