

SAFETY DATA SHEET

Date issued: 02/16/2015

MONTANA® MP2675 ACTIVATOR

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code MP2675 **Product Name ACTIVATOR**

Recommended use A paint or paint constituent product

UNITED STATES OF AMERICA

Manufacturer

Company Name ChemSpec USA, Inc. Address 9287 Smucker Road

Orrville, Ohio 44667

1 330 669 8512 Telephone **Facsimile** 1 330 669 3965

Emergency Contact

Contact Name CHEMTREC 1-800-424-9300 Contact number

SECTION 2. HAZARDS IDENTIFICATION

HAZARDOUS MIXTURE, DANGEROUS GOODS **Overall Nature**

Classification reference SANS10234 (1272/2008/EC):

Classification of the substance or mixture

Flammable liquids, Hazard Category 3
Acute toxicity (dermal), Hazard Category 5
Acute toxicity (inhalation), Hazard Category 4
Skin corrosion/irritation, Hazard Category 2
Sensitization ^ Respiration, Hazard Category 1 (H226) (H313) (H332) (H315) (H334)Carcinogenicity, Hazard Category 2 (H351)

GHS label elements, including precautionary statements

Signal word Danger

Pictograms



Hazard and Precautionary Statements

Hazard Statements

Flammable liquid and vapor

May be harmful in contact with skin

Harmful if inhaled

Causes skin irritation

May cause allergy or asthma symptoms or breathing difficulties if inhaled

Suspected of causing cancer

Precautionary Statements

Prevention Statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment. – if the explosive is electrostatically sensitive.

Use explosion-proof electrical/ventilating/lighting/.../ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash ... thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

SDS: ACTIVATOR Date issued: 02/16/2015 Rev. Date: 07/20/2016 Page 1 of 6 In case of inadequate ventilation wear respiratory protection.

Response Statements

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF exposed or concerned: Get medical advice/ attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see ... on this label). ... Reference to supplemental first aid instruction.

If skin irritation occurs: Get medical advice/ attention.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Take off contaminated clothing and wash before reuse.

In case of fire: Use powder/... for extinction.

Storage Statements

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal Statements

Dispose of contents/container in accordance with local/regional/ national/international regulations in accordance with local/regional/ national/international regulation

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product type: Mixture Generic name: PAINT or PAINT RELATED MATERIAL CAS No.: Not applicable EU Index No: Not applicable UN No: 1263

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	% m/m	EC Labels	CAS Number	EC Index
XYLENE	30-60 %	Xn	1330-20-7	601-022-00-9
n-BUTYL ACETATE	1-5 %		123-86-4	607-025-00-1
TOLUENE DI-ISOCYANATE MIXED ISOMERS.				
	0.1-1.0 %	T+	26471-62-5	615-006-00-4
5-METHYLHEXAN-2-ONE	<25 %	- Xn	110-12-3	606-026-00-4
AROMATIC HYDROCARBON SOLVENT	<20 %	Xn		0

Classification reference SANS10234 (1272/2008/EC):

EC Index Classification | Hazard Code |

601-022-00-9 Flam. Liq. 3;Acute Tox. 4 ;Acute Tox. 4 ;Skin Irrit. 2 | H226;H332;H312;H315 |

607-025-00-1 Flam. Liq. 3;STOT SE 3 | H226;H336 |

615-006-00-4 Carc. 2; Acute Tox. 2; Eye Irrit. 2; STOT SE 3; Skin Irrit. 2; Resp. Sens. 1; Skin Sens. 1; Aquatic Chronic 3 |

H351;H330;H319;H335;H315;H334;H317;H412

606-026-00-4 Flam. Liq. 3;Acute Tox. 4 | H226;H332 |

o not found in T31 | |

SECTION 4. FIRST AID MEASURES

Inhalation Move to fresh air. In case of any discomfort seek medical attention immediately.

Skin Drench with water. Remove contaminated clothing. Use a skin cleaner. In severe cases refer to Doctor.

Eyes ACT FAST! Rinse immediately with plenty of water. Refer immediately to Doctor.

Ingestion Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical advice.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:

Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets.

Specific hazards arising from the chemical:

Containers can burst in a fire. Can form explosive vapor/air mixture. Static discharge hazard!

Flammable with toxic fumes.

Cool containers in case of fire.

Special protective actions for fire-fighters:

Suitable extinguishing media: Foam, dry agent

Substance reacts violently/is explosive

For fires use breathing apparatus. If no fire, breathing apparatus not essential Prevent, by any means available, spillage from entering drains or water courses

SECTION 6. ACCIDENTAL RELEASE MEASURES

Contain & collect. Use an inert - NOT sawdust. Keep out of drains & sewers.

Wear protective equipment (see Section 8). Keep unprotected persons away.

Do not allow product to reach sewage system or any water course.

Remove ignition sources and provide sufficient ventilation

SECTION 7. HANDLING AND STORAGE

Storage:

Store separately from: explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

No open flames. No smoking.

SDS: ACTIVATOR Date issued: 02/16/2015 Rev. Date: 07/20/2016 Page 2 of 6

Keep containers cool. Avoid free fall of liquid - use earthing. Subject to local bylaws

Handling:

Ensure good ventilation/exhaustion at the workplace

Do not spray on a naked flame or any incandescent material

Eating, drinking and smoking in work areas is prohibited

Wash hands after use

Remove contaminated clothing and protective equipment before entering eating areas

Inhalation Use respiratory protection. Handle with extreme care. Absorb any spillage at once.

Skin AVOID CONTACT. Use impervious gloves, apron and boots.

Eves Use goggles. Avoid direct contact.

Ingestion Observe the rules of hygiene. Wash before eating, drinking or smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	CAS Number	TWA OEL	TWA OEL	STOEL	STOEL	OEL	Vap.Press.
	-	(mg/m3)	(ppm)	(mg/m3)	(ppm)	Type	(mmHg)
ACTIVATOR	Not applicable						
Components :							
XYLÈNE	1330-20-7	435	100	650.	150.	RL+ S	6.7
n-BUTYL ACETATE	123-86-4	710.	150.	950	200	RL	8.7
TOLUENE DI-ISOCYANATE MIXED ISOMERS.							
	26471-62-5			0.070		CL S	.01
5-METHYLHEXAN-2-ONE	110-12-3	240.	50.	360	75	RL	
	(CL/RL = Controlled/Recommended level 'S' = Skin annotation)						

OEL Type: Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary

Appropriate hand protection and protective clothing must always be used

Keep away from foodstuffs, beverages and feed Wash hands before breaks and at the end of work

Paint Type Mixture of synthetic resins, pigments and solvents

General PPE Requirements For Mixing, Brush Application, Roller Application, Pouring, etc.

Personal protective equipment:

Skin PPE: Overall and impervious gloves (e.g. nitrile rubber) **Respiratory PPE**: Air purifying respirator (e.g. cartridge type)

Eye PPE: Face shield or solvent resistant goggles

HMIS Rating (USA) 2 - 3 - 0 - I (Health-Flam-Reactivity-PPE)

SAPMA Rating 2-H-E PPE: Gloves, Respirator and Eye protection









SPRAY BOOTH

Spray booth Type Spray booth complying with National Standards

Skin PPE Nitrile Gloves

Eyes PPE Face shield or solvent resistant goggles

Respiratory Protection Air supplied full face piece or head covering respirator suitable for organic vapors/particulates

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Property Appearance Value Viscous liquid Odor Pungent not available >35°C рН Boiling point not available Melting point Flash point >23°C not available Explosive prop Oxidizing prop not available Vapor pressure not available Density not available Water solubility not available not available Fat solubility Partition coefficient not available Viscosity not available Vapor density not available

 Evaporation rate
Auto ignition temperature
L.E.L.
U.E.L.
voi available
not available
not available
not available
not available
4.81 lbs./qal (576 g/

Regulatory VOC 4.81 lbs./gal (576 g/L) Actual VOC

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions

Could generate static - USE EARTHING

No reaction with fire-fighting water

Keep away from: explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

SECTION 11. TOXICOLOGICAL INFORMATION

Name CAS Number LD50 Oral LD50 Skin LC50 Inhal(gas) LC50 Inhal(mist) - mg/kg mg/kg ppmV mg/lt l

ACTIVATOR Not applicable >500

n-BUTYL ACETATE 123-86-4 14000 mg (Rat) >5000 mg (Rabbit) TOLUENE DI-ISOCYANATE MIXED ISOMERS.

26471-62-5 6170 mg (Rat)

5-METHYLHEXAN-2-ONE 110-12-3

InhalationHARMFUL. Contains ISOCYANATE. Sensitizer with accumulative effects.SkinHighly irritating.Risk of dermatitis. May be absorbed through intact skin.

Eyes Highly Irritating. Risk of dermatitis. May be absorbed through intact

Highly Irritating and risk of irreversible damage.

Ingestion Harmful if swallowed. Can affect CNS. Systemic poison.

SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove Aquatic toxicity: No further relevant information available Persistence and degradability: No further relevant information available. Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Available ecological data of ingredients:

Name CAS Number Aquatic Toxicity

XYLENE 1330-20-7 LC50 (goldfish) = 13 mg/L; 24 hr

LC50 (rainbow trout) = 13.5 mg/L; 96 h EC50 Daphnia magna 3.82 mg/L, 48 h

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers. Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

SECTION 14. TRANSPORT INFORMATION

UN Number 1263

Shipping Name PAINT or PAINT RELATED MATERIAL

 IMO Class
 3.3

 Packing Group
 III

 Action Code
 127

 HazChem
 3[Y]

 Kemler Code
 30

USA (DOT) UN1263 **CANADA (TDG)** UN1263



SECTION 15. REGULATORY INFORMATION

CANADIAN DSL INVENTORY Components are listed on inventory list **USA TSCA INVENTORY** Components are listed on inventory list

 B-2: Flammable liquid with Flash Point lower than 37.8°C (100°F)

D-2B: Material causing other toxic effects

SECTION 16. OTHER INFORMATION

CONTAINS ISOCYANATE - POTENTIAL SENSITISER - ENSURE PRECAUTIONS ARE TAKEN. IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE PAY SPECIAL ATTENTION TO STORAGE AND HANDLING REQUIREMENTS. HMIS Rating (USA): 2 - 3 - 0 - I (Health-Flam-Reactivity-PPE)

Hazard (H) phrases associated with components

H226: Flammable liquid and vapor H312: Harmful in contact with skin H315: Causes skin irritation H317: May cause an allergic skin reaction H319: Causes serious eye irritation H330 : Fatal if inhaled H332: Harmful if inhaled H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled H335: May cause respiratory irritation H336: May cause drowsiness or dizziness H351: Suspected of causing cancer H412: Harmful to aquatic life with long lasting effects

Abbreviations

SDS: Safety Data Sheet

STOEL: Short-term occupational exposure limit

STOT-RE: Specific Target Organ Toxicity - Repeated Exposure

STOT-SE: Specific Target Organ Toxicity - Single Exposure

```
Code: Abbreviation: Meaning
 : : flammable
T+::very toxic Xn::harmful
    : Associated pictogram code shown in brackets
H226 : Flam. Liq. 3 : (GHS02) Flammable liquids, Hazard Category 3
H312 : Acute Tox. 4 : (GHS07) Acute toxicity (dermal), Hazard Category 4
H315 : Skin Corr/Irrit. 2 : (GHS07) Skin corrosion/irritation, Hazard Category 2
H317: Skin Sens. 1: (GHS07) Sensitization ^ Skin, Hazard Category 1
H319: Eye Dam/Irrit 2: (GHS07) Serious eye damage/eye irritation, Hazard Category 2
H330: Acute Tox. 1: (GHS06) Acute toxicity (inhalation), Hazard Category 1
H332: Acute Tox. 4: (GHS07) Acute toxicity (inhalation), Hazard Category 1
H334: Resp. Sens. 1: (GHS08) Sensitization ^ Respiration, Hazard Category 1
H335: STOT SE 3: (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation
H336: STOT SE 3: (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Narcosis
H331: Carc. 2: (GHS08) Carcinogenicity, Hazard Category 2
H412 : Aquatic Chronic 3 : (none) Hazardous to the aquatic environment ^ Chronic Hazard, Category 3
: %m/m : Percent by mass : ACGIH : American Conference of Governmental Industrial Hygienist
  ATE : Acute Toxicity Estimate
  CAS: Chemical Abstracts Service
CHIP: Chemicals (Hazard Information and Packaging for supply)
CLP: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
  CNS : Central Nervous System
DIN : Standard of the German Institute for Standardization
  DOT : Department of Transport
  EC50 : Effective Concentration (Median) for 50% of the response under test
  ECB : European Chemicals Bureau
ECHA : European Chemicals Agency, Helsinki (http://echa.europa.eu/home_en.asp)
  EEC: European Economic Community
EINECS: European Inventory of Existing Chemical Substances
ELINCS: European List of Notified Chemical Substances
  GHS : Globally Harmonized System of Classification and Labelling of Chemicals HMIS : Hazardous Materials Information System (USA only)
  IATA: International Air Transport Association
IMDG: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
 : INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007 : ISO : International Standards Organization
  L.E.L. : Lower explosive limit
LD50/LC50 : Median (50%) lethal dose/concentration
  mg/m3 : Milligrams per cubic meter
MSDS : Material safety data sheet
n./a. : Not available
  NC: No Classification
  No : Number
OEL : Occupational exposure limit
 : OEL-GL : Occupational exposure limit - control limit
: OEL-RL : Occupational exposure limit - recommended limit
: OHS Act : Occupational Health and Safety Act
  P statement : Precautionary statement
PEL : Permissible Exposure Limit
  PPE: Personal protective equipment
  ppm : Parts per million
   REACH: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals
  RTDG: Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG) SABS: South African Bureau of Standards
   SANS: South African National Standards
  SAPMA : South African Paint Manufacturers Association SARA 313 : Toxic Release Inventory Reporting SRA Section 3
```

SDS: ACTIVATOR Date issued: 02/16/2015 Rev. Date: 07/20/2016 Page 5 of 6 : TDG : Transport of Dangerous Goods

- : TDG: 1 ransport of Dangerous Goods
 : TSCA: Toxic Substance Control Act (USA only)
 : TWA: Time weighted average
 : U.E.L.: Upper explosive limit
 : UN: United Nations
 : WHMIS: Workplace Hazardous Materials Information Systems (Canada only)

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009) OEL's derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42). All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.

While all information is accurate to the best of our knowledge, we continue updating ALL SDS document formats in accordance with the most recent GHS mandated changes.

(Date of issue: 2/16/2015 Date of Revision: 07/20/2016)

Date issued: 02/16/2015 SDS: ACTIVATOR Rev. Date: 07/20/2016 Page 6 of 6