



SAFETY DATA SHEET

Date issued: 02/16/2015

MONTANA® PS3203 PRIMER SURFACER

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code	PS3203	Product Name	PRIMER SURFACER
Recommended use	A paint or paint constituent product		
UNITED STATES OF AMERICA			
Manufacturer			
Company Name	ChemSpec USA, Inc.		
Address	9287 Smucker Road Orrville, Ohio 44667		
Telephone	1-330-669-8512		
Facsimile	1-330-669-3965		
Emergency Contact			
Contact Name	CHEMTREC		
Contact Number	1-800-424-9300		

SECTION 2. HAZARDS IDENTIFICATION

Overall Nature HAZARDOUS MIXTURE, DANGEROUS GOODS

Classification reference SANS10234 (1272/2008/EC) :

Classification of the substance or mixture

- (H226) Flammable liquids, Hazard Category 3
- (H315) Skin corrosion/irritation, Hazard Category 2
- (H401) Hazardous to the aquatic environment ^ Acute Hazard, Category 1

GHS label elements, including precautionary statements

Signal word **Warning**

Pictograms



Hazard and Precautionary Statements

Hazard Statements

- Flammable liquid and vapor
- Causes skin irritation
- Very toxic to aquatic life

Precautionary Statements

Prevention Statements

- Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment. – if the explosive is electrostatically sensitive.
- Use explosion-proof electrical/ventilating/lighting/.../ equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Wash ... thoroughly after handling.
- Avoid release to the environment. – if this is not the intended use.
- Wear protective gloves/protective clothing/eye protection/face protection.

Response Statements

- IF ON SKIN: Wash with plenty of soap and water.
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- Specific treatment (see ... on this label). ... Reference to supplemental first aid instruction.
- If skin irritation occurs: Get medical advice/ attention.
- Take off contaminated clothing and wash before reuse.
- In case of fire: Use powder/... for extinction.
- Collect spillage.

Storage Statements

Store in a well-ventilated place. Keep cool.

Disposal Statements

Dispose of contents/container in accordance with local/regional/ national/international regulations in accordance with local/regional/ national/international regulation

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Product type :** Mixture **Generic name :** PAINT or PAINT RELATED MATERIAL**CAS No. :** Not applicable **EU Index No :** Not applicable **UN No :** 1263**HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS**

Name	% m/m	EC Labels	CAS Number	EC Index
XYLENE	10-30 %	Xn	1330-20-7	601-022-00-9
n-BUTYL ACETATE	1-5 %		123-86-4	607-025-00-1
ZINC (ORTHO) PHOSPHATE	2.5-25 %	N	7779-90-0	o
2-METHOXY-1-METHYLETHYL ACETATE	<20 %	-	108-65-6	607-195-00-7
5-METHYLHEXAN-2-ONE	<25 * %	- Xn	110-12-3	606-026-00-4
WHITE SPIRIT (WS3)	<10 * %	Xn	64742-88-7	649-405-00-X
4-METHYLPENTAN-4-ONE	<20 * %	F Xn	108-10-1	606-004-00-4

Classification reference SANS10234 (1272/2008/EC) :

EC Index	Classification Hazard Code
601-022-00-9	Flam. Liq. 3;Acute Tox. 4 ;Acute Tox. 4 ;Skin Irrit. 2 H226;H332;H312;H315
607-025-00-1	Flam. Liq. 3;STOT SE 3 H226;H336
	o not found in T31
607-195-00-7	Flam. Liq. 3 H226
606-026-00-4	Flam. Liq. 3;Acute Tox. 4 H226;H332
649-405-00-X	Asp. Tox. 1 H304
606-004-00-4	Flam. Liq. 2;Acute Tox. 4 ;Eye Irrit. 2;STOT SE 3 H225;H332;H319;H335

SECTION 4. FIRST AID MEASURES

Inhalation	Move to fresh air.
Skin	Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention
Eyes	Rinse immediately with plenty of water. Seek medical advice if symptoms persist.
Ingestion	Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical attention.

SECTION 5. FIRE FIGHTING MEASURES**Suitable extinguishing media :**

Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets.

Specific hazards arising from the chemical :

Containers can burst in a fire. Can form explosive vapor/air mixture. Static discharge hazard!

Flammable with toxic fumes.

Cool containers in case of fire.

Special protective actions for fire-fighters :

Suitable extinguishing media : Foam, dry agent

Substance reacts violently/is explosive

For fires use breathing apparatus. If no fire, breathing apparatus not essential

Prevent, by any means available, spillage from entering drains or water courses

SECTION 6. ACCIDENTAL RELEASE MEASURES

Contain & collect. Use an inert - NOT sawdust. Keep out of drains & sewers.

Wear protective equipment (see Section 8). Keep unprotected persons away.

Do not allow product to reach sewage system or any water course.

Remove ignition sources and provide sufficient ventilation

SECTION 7. HANDLING AND STORAGE**Storage :**

Store separately from : explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

No open flames. No smoking.

Keep containers cool. Avoid free fall of liquid - use earthing.

Subject to local bylaws

Handling :

Ensure good ventilation/exhaustion at the workplace

Do not spray on a naked flame or any incandescent material

Eating, drinking and smoking in work areas is prohibited

Wash hands after use

Remove contaminated clothing and protective equipment before entering eating areas

Inhalation	In case of insufficient ventilation, use suitable respiratory protection.
Skin	Use barrier cream and impervious gloves.
Eyes	Use face shield & goggles or full face respirator/hood. Avoid direct contact.
Ingestion	Observe the rules fo hygiene. Wash before eating, drinking or smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	CAS Number	TWA OEL (mg/m3)	TWA OEL (ppm)	STOEL (mg/m3)	STOEL (ppm)	OEL Type	Vap.Press. (mmHg)
PRIMER SURFACER	Not applicable						
Components :							
XYLENE	1330-20-7	435	100	650.	150.	RL+ S	6.7
n-BUTYL ACETATE	123-86-4	710.	150.	950	200	RL	8.7
ZINC (ORTHO) PHOSPHATE	7779-90-0	10/4				T/R	
2-METHOXY-1-METHYLETHYL ACETATE	108-65-6						
5-METHYLHEXAN-2-ONE	110-12-3	240.	50.	360	75	RL	
WHITE SPIRIT (WS3)	64742-88-7	575	100	720	125	RL	
4-METHYLPENTAN-4-ONE	108-10-1	205	50	300	75	RL+ S	16

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

OEL Type : Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary

Appropriate hand protection and protective clothing must always be used

Keep away from foodstuffs, beverages and feed

Wash hands before breaks and at the end of work

Paint Type Mixture of synthetic resins, pigments and solvents

General PPE Requirements For Mixing, Brush Application, Roller Application, Pouring, etc.

Personal protective equipment :

Skin PPE : Overall and impervious gloves (e.g. nitrile rubber)

Respiratory PPE : Air purifying respirator (e.g. cartridge type)

Eye PPE : Face shield or solvent resistant goggles

HMIS Rating (USA) 1 - 3 - 0 - I (Health-Flam-Reactivity-PPE)

SAPMA Rating 3-H-E PPE : Gloves, Respirator and Eye protection



SPRAY BOOTH

Spray booth Type Spray booth complying with National Standards

Skin PPE Nitrile Gloves

Eyes PPE Face shield or solvent resistant goggles

Respiratory Protection Air supplied full face piece or head covering respirator suitable for organic vapors/particulates

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Appearance	Viscous liquid
Odor	Pungent
pH	not available
Boiling point	>35°C
Melting point	not available
Flash point	>23°C
Explosive prop	not available
Oxidizing prop	not available
Vapor pressure	not available
Density	not available
Water solubility	not available
Fat solubility	not available
Partition coefficient	not available
Viscosity	not available
Vapor density	not available
Evaporation rate	not available
Auto ignition temperature	not available
L.E.L.	not available
U.E.L.	not available
% non volatile	not available
Regulatory VOC	3.66 lbs./gal (439 g/L)
Actual VOC	3.66 lbs./gal (439 g/L)

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions
 Could generate static - USE EARTHING
 No reaction with fire-fighting water
 Keep away from : explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

SECTION 11. TOXICOLOGICAL INFORMATION

Name	CAS Number	LD50 Oral mg/kg	LD50 Skin mg/kg	LC50 Inhal(gas) ppmV	LC50 Inhal(mist) mg/ltr
- PRIMER SURFACER	- Not applicable	- >500	- >500	- >5000 mg (Rabbit)	- >5000 mg (Rabbit)
Components :					
XYLENE	1330-20-7	4300 mg (Rat)	5000 mg (Rabbit)		
n-BUTYL ACETATE	123-86-4	14000 mg (Rat)	>5000 mg (Rabbit)		
ZINC (ORTHO) PHOSPHATE	7779-90-0				
2-METHOXY-1-METHYLETHYL ACETATE	108-65-6				
5-METHYLHEXAN-2-ONE	110-12-3				
WHITE SPIRIT (WS3)	64742-88-7				
4-METHYLPENTAN-4-ONE	108-10-1	2080 mg (Rat)			

Inhalation Irritating.
Skin Irritating, risk of dermatitis. May be absorbed.
Eyes Irritating.
Ingestion Irritating and nauseating.

SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove
 Aquatic toxicity : No further relevant information available
 Persistence and degradability : No further relevant information available.
 Bioaccumulative potential : No further relevant information available.
 Mobility in soil : No further relevant information available.

Available ecological data of ingredients :

Name	CAS Number	Aquatic Toxicity
XYLENE	1330-20-7	LC50 (goldfish) = 13 mg/L; 24 hr LC50 (rainbow trout) = 13.5 mg/L; 96 h EC50 Daphnia magna 3.82 mg/L, 48 h

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

SECTION 14. TRANSPORT INFORMATION

UN Number 1263
Shipping Name PAINT or PAINT RELATED MATERIAL
IMO Class 3.3
Packing Group III
Action Code 127
HazChem 3[Y]
Kemler Code 30

USA (DOT) UN1263
CANADA (TDG) UN1263



SECTION 15. REGULATORY INFORMATION

CANADIAN DSL INVENTORY Components are listed on inventory list
USA TSCA INVENTORY Components are listed on inventory list

Canada WHMIS
B-2 : Flammable liquid with Flash Point lower than 37.8°C (100°F)
D-2B : Material causing other toxic effects

SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES.
IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.
HMIS Rating (USA) : 1 - 3 - 0 - I (Health-Flam-Reactivity-PPE)

Hazard (H) phrases associated with components

H225 : Highly flammable liquid and vapor
H226 : Flammable liquid and vapor
H304 : May be fatal if swallowed and enters airways
H312 : Harmful in contact with skin
H315 : Causes skin irritation
H319 : Causes serious eye irritation
H332 : Harmful if inhaled
H335 : May cause respiratory irritation
H336 : May cause drowsiness or dizziness

Abbreviations

Code : Abbreviation : Meaning
- : : flammable
F : : highly flammable
N : : dangerous for the environment
Xn : : harmful
=====
: : Associated pictogram code shown in brackets
H225 : Flam. Liq. 2 : (GHS02) Flammable liquids, Hazard Category 2
H226 : Flam. Liq. 3 : (GHS02) Flammable liquids, Hazard Category 3
H304 : Asp. Tox. 1 : (GHS08) Aspiration hazard, Hazard Category 1
H312 : Acute Tox. 4 : (GHS07) Acute toxicity (dermal), Hazard Category 4
H315 : Skin Corr/Irrit. 2 : (GHS07) Skin corrosion/irritation, Hazard Category 2
H319 : Eye Dam/Irrit 2 : (GHS07) Serious eye damage/eye irritation, Hazard Category 2
H332 : Acute Tox. 4 : (GHS07) Acute toxicity (inhalation), Hazard Category 4
H335 : STOT SE 3 : (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation
H336 : STOT SE 3 : (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Narcosis
=====
: : %m/m : Percent by mass
: : ACGIH : American Conference of Governmental Industrial Hygienist
: : ATE : Acute Toxicity Estimate
: : CAS : Chemical Abstracts Service
: : CHIP : Chemicals (Hazard Information and Packaging for supply)
: : CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
: : CNS : Central Nervous System
: : DIN : Standard of the German Institute for Standardization
: : DOT : Department of Transport
: : EC : European Community
: : EC50 : Effective Concentration (Median) for 50% of the response under test
: : ECB : European Chemicals Bureau
: : ECHA : European Chemicals Agency, Helsinki (http://echa.europa.eu/home_en.asp)
: : EEC : European Economic Community
: : EINECS : European Inventory of Existing Chemical Substances
: : ELINCS : European List of Notified Chemical Substances
: : GHS : Globally Harmonized System of Classification and Labelling of Chemicals
: : HMIS : Hazardous Materials Information System (USA only)
: : IATA : International Air Transport Association
: : IMDG : International Maritime Dangerous Goods Code
: : IMO : International Maritime Organization
: : INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007
: : ISO : International Standards Organization
: : L.E.L. : Lower explosive limit
: : LD50/LC50 : Median (50%) lethal dose/concentration
: : mg/m3 : Milligrams per cubic meter
: : MSDS : Material safety data sheet
: : n/a. : Not available
: : NC : No Classification
: : No : Number
: : OEL : Occupational exposure limit
: : OEL-CL : Occupational exposure limit - control limit
: : OEL-RL : Occupational exposure limit - recommended limit
: : OHS Act : Occupational Health and Safety Act
: : P statement : Precautionary statement
: : PEL : Permissible Exposure Limit
: : PPE : Personal protective equipment
: : ppm : Parts per million
: : REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals
: : RTDG : Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG)
: : SABS : South African Bureau of Standards
: : SANS : South African National Standards
: : SAPMA : South African Paint Manufacturers Association
: : SARA 313 : Toxic Release Inventory Reporting SRA Section 3
: : SDS : Safety Data Sheet
: : STOEL : Short-term occupational exposure limit
: : STOT-RE : Specific Target Organ Toxicity - Repeated Exposure
: : STOT-SE : Specific Target Organ Toxicity - Single Exposure
: : TDG : Transport of Dangerous Goods
: : TSCA : Toxic Substance Control Act (USA only)
: : TWA : Time weighted average
: : U.E.L. : Upper explosive limit
: : UN : United Nations
: : WHMIS : Workplace Hazardous Materials Information Systems (Canada only)
=====
: :

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)
OEL's derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42). All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.

While all information is accurate to the best of our knowledge, we continue updating ALL SDS document formats in accordance with the most recent GHS mandated changes.

(Date of issue: 02/16/2015 Date of Revision: 07/20/2016)