

# SAFETY DATA SHEET

Date issued: 02/16/2015

# **MONTANA® PA3040E CATALYST**

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Code** PA3040E **Product Name CATALYST** 

Recommended use A paint or paint constituent product

**UNITED STATES OF AMERICA** 

Manufacturer

**Company Name** ChemSpec USA, Inc.

9287 Smucker Road

**Address** Orrville, Ohio

44667

Telephone 1-330-669-8512 **Facsimile** 1-330-669-3965

**Emergency Contact** 

**Contact Name** CHEMTREC **Contact Number** 1-800-424-9300

## **SECTION 2. HAZARDS IDENTIFICATION**

HAZARDOUS MIXTURE, DANGEROUS GOODS **Overall Nature** 

Classification reference SANS10234 (1272/2008/EC):

Classification of the substance or mixture

Flammable liquids, Hazard Category 2
Acute toxicity (oral), Hazard Category 4
Skin corrosion/irritation, Hazard Category 2
Serious eye damage/eye irritation, Hazard Category 1
Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation
Aspiration hazard, Hazard Category 1 (H225) (H302) (H315)

(H318)

(H335)

(H304)

Hazardous to the aquatic environment ^ Acute Hazard, Category 1 Hazardous to the aquatic environment ^ Chronic Hazard, Category 1 (H400)(H410)

### GHS label elements, including precautionary statements

Signal word Danger

**Pictograms** 



#### **Hazard and Precautionary Statements**

**Hazard Statements** 

Highly flammable liquid and vapor

Harmful if swallowed

Causes skin irritation

Causes serious eye damage

May cause respiratory irritation

May be fatal if swallowed and enters airways

Very toxic to aquatic life

Very toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention Statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment. – if the explosive is electrostatically sensitive.

Use explosion-proof electrical/ventilating/lighting/.../ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash ... thoroughly after handling.

Do not eat, drink or smoke when using this product.

SDS: ACTIVATOR Date issued: 2/16/2015 Rev. Date: 07/20/2016 Page 1 of 6 Use only outdoors or in a well-ventilated area.

Avoid release to the environment. - if this is not the intended use.

Wear protective gloves/protective clothing/eye protection/face protection.

#### Response Statements

### STATE | PRINCE | Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Specific treatment (see ... on this label). ... Reference to supplemental first aid instruction.

Rinse mouth.

Do NOT induce vomiting.

If skin irritation occurs: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use powder/... for extinction.

Collect spillage.

Storage Statements

Store in a well-ventilated place. Keep container tightly closed. - if product is volatile so as to generate hazardous atmosphere.

Store in a well-ventilated place. Keep cool.

Store locked up

Disposal Statements

Dispose of contents/container in accordance with local/regional/ national/international regulations in accordance with local/regional/ national/international

### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Generic name: PAINT or PAINT RELATED MATERIAL Product type: Mixture CAS No.: Not applicable **EU Index No :** Not applicable **UN No:** 1263 HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

**EC** Labels CAS Number EC Index N-BUTANOL 30-60 % Xn 71-36-3 603-004-00-6 P-CHLOROBENZOTRIFLUORIDE 10-30 % Xn N 98-56-6 202-681-1 10-30 % F Xn N 142-82-5 601-008-00-2 **EPOXY POLYAMIDE HARDENER 100% SOLIDS** 10-30 % Xn F Xi 67-64-1 606-001-00-8 <20 %

#### Classification reference SANS10234 (1272/2008/EC):

Classification | Hazard Code | FC Index

Flam. Liq. 3; Acute Tox. 4; STOT SE 3; Skin Irrit. 2; Eye Dam. 1; STOT SE 3 | H226; H302; H335; H315; H318; H336 | 603-004-00-6 Acute Tox. 4 ;Eye Irrit. 2;STOT SE 3;Skin Irrit. 2;Aquatic Acute 1;Aquatic Chronic 1 | H302;H319;H335;H315;H400;H410 | Flam. Liq. 2;Asp. Tox. 1;Skin Irrit. 2;STOT SE 3;Aquatic Acute 1;Aquatic Chronic 1 | H225;H304;H315;H336;H400;H410 | 202-681-1 601-008-00-2 Flam. Liq. 2;Eye Irrit. 2;STOT SE 3 | H225;H319;H336 | 606-001-00-8

## **SECTION 4. FIRST AID MEASURES**

Inhalation Move to fresh air. In case of discomfort seek medical attention.

Skin Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention

Eyes Rinse well with water and seek medical advice if discomfort persists.

Ingestion Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical advice.

### **SECTION 5. FIRE FIGHTING MEASURES**

### Suitable extinguishing media:

Foam. Dry powder. Fog to cool and control. Do NOT use water jets.

## Specific hazards arising from the chemical:

Containers can burst in a fire. Can form explosive vapor/air mixture. Static discharge hazard!

Highly flammable with toxic fumes.

Cool containers in case of fire.

## Special protective actions for fire-fighters:

Suitable extinguishing media: Foam, dry agent

Substance reacts violently/is explosive

For fires use breathing apparatus. If no fire, breathing apparatus not essential Prevent, by any means available, spillage from entering drains or water courses

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Contain & collect. Use an Inert NOT sawdust. Keep waste separate for disposal.

Wear protective equipment (see Section 8). Keep unprotected persons away.

Do not allow product to reach sewage system or any water course.

Remove ignition sources and provide sufficient ventilation

SDS: ACTIVATOR Date issued: 2/16/2015 Rev. Date: 07/20/2016 Page 2 of 6

### **SECTION 7. HANDLING AND STORAGE**

#### Storage:

Store separately from: explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards).

No open flames. No smoking. No sparks.

Keep containers cool. Avoid free fall of liquid - use earthing.

Subject to local bylaws

#### Handling:

Ensure good ventilation/exhaustion at the workplace

Do not spray on a naked flame or any incandescent material

Eating, drinking and smoking in work areas is prohibited

Wash hands after use

Remove contaminated clothing and protective equipment before entering eating areas

**Inhalation** In case of insufficient ventilation, use suitable respiratory protection. **Skin** Avoid direct contact. Use barrier cream and impervious gloves.

**Eyes** Avoid any form of direct contact. Do not touch eyes with dirty hands or gloves. **Ingestion** Observe the rules of hygiene. Wash before eating, drinking or smoking.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	CAS Number	TWA OEL	TWA OEL	STOEL	STOEL	OEL	Vap.Press.
	-	(mg/m3)	(ppm)	(mg/m3)	(ppm)	Type	(mmHg)
ACTIVATOR	Not applicable	е					
Components:							
N-BUTANOL	71-36-3	150	50	150	50	RL S	1.3
P-CHLOROBENZOTRIFLUORIDE	98-56-6	300	50	300	50	RL	
n-HEPTANE	142-82-5	1600	400.	2000	500	RL	13
ACETONE	67-64-1	1780	750	3560	1500	RL	181
	(CL/RL = Controlled/Recommended level 'S' = Skin annotation)						

OEL Type : Mixture Skin Sensitizer

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary

Appropriate hand protection and protective clothing must always be used

Keep away from foodstuffs, beverages and feed Wash hands before breaks and at the end of work

Paint Type Mixture of synthetic resins, pigments and solvents

General PPE Requirements For Mixing, Brush Application, Roller Application, Pouring, etc.

## Personal protective equipment :

**Skin PPE**: Overall and impervious gloves (e.g. nitrile rubber) **Respiratory PPE**: Air purifying respirator (e.g. cartridge type)

Eye PPE: Face shield or solvent resistant goggles

HMIS Rating (USA) 2 - 4 - 0 - I (Health-Flam-Reactivity-PPE)

SAPMA Rating 2-H-E PPE : Gloves, Respirator and Eye protection









SPRAY BOOTH

Spray booth Type Spray booth complying with National Standards

Skin PPE Nitrile Gloves

**Eyes PPE** Face shield or solvent resistant goggles

**Respiratory Protection** Air supplied full face piece or head covering respirator suitable for organic vapors/particulates

### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Value Property Appearance Viscous liquid Odor Pungent not available рΗ >35°C Boiling point Melting point not available <-18°C Flash point Explosive prop not available

SDS: ACTIVATOR Date issued: 2/16/2015 Rev. Date: 07/20/2016 Page 3 of 6

Oxidizing prop not available Vapor pressure not available not available Density Water solubility not available Fat solubility
Partition coefficient not available not available Viscosity not available Vapor density not available Evaporation rate not available Auto ignition temperature not available L.E.L. not available U.E.L. not available % non volatile not available Regulatory VOC 5.60 lbs./gal (671 g/L) Actual VOC 4.60 lbs./gal (551 g/L)

### **SECTION 10. STABILITY AND REACTIVITY**

Stable under normal conditions

Prone to ignite by static

No reaction with fire-fighting water

Keep away from : explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

### **SECTION 11. TOXICOLOGICAL INFORMATION**

 Name
 CAS Number
 LD50 Oral mg/kg
 LD50 Skin mg/kg
 LC50 Inhal(gas) ppmV
 LC50 Inhal(mist) mg/lt

N-BUTANOL 71-36-3 790 mg (Rat) 3400 mg (Rabbit)

 P-CHLOROBENZOTRIFLUORIDE
 98-56-6
 <500 mg</td>

 n-HEPTANE
 142-82-5
 >5000 mg (Rat)

 ACETONE
 67-64-1
 9750 mg (Rat)

Inhalation HARMFUL. Excessive exposure to this material must be avoided.

Skin HARMFUL BY CONTACT. Potential sensitizer.

Eyes Irritating - may cause damage if not given prompt attention.

Ingestion Harmful if swallowed.

Skin Sensitizer

## **SECTION 12. ECOLOGICAL INFORMATION**

May have short term environmental effects. Contain, monitor & remove Aquatic toxicity: No further relevant information available Persistence and degradability: No further relevant information available. Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Available ecological data of ingredients:

Name CAS Number Aquatic Toxicity

N-BUTANOL 71-36-3 LC50 Pimephales promelas 1,730 mg/l 96 h

EC50 Daphnia magna: 1,983 mg/l; 48 h EC50 Daphnia magna: 1,983 mg/l; 48 h

P-CHLOROBENZOTRIFLUORIDE 98-56-6 LC50 (guppy) = 5.9 mg/L; 14 d LC50 (P.prom, F.min)=57 mg/L;96 h

LC50 (P.prom, F.min)=57 mg/L;96 h EC50 Daphnia magna 68 mg/L, 48 h EC50 (Algae) 14mg/L: 48h

### **SECTION 13. DISPOSAL INFORMATION**

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

# **SECTION 14. TRANSPORT INFORMATION**

UN Number 1263

Shipping Name PAINT or PAINT RELATED MATERIAL

 IMO Class
 3.2

 Packing Group
 II

 Action Code
 127

 HazChem
 3[Y]E

 Kemler Code
 30

USA (DOT) UN1263 CANADA (TDG) UN1263

SDS: ACTIVATOR Date issued: 2/16/2015 Rev. Date: 07/20/2016 Page 4 of 6



## **SECTION 15. REGULATORY INFORMATION**

**CANADIAN DSL INVENTORY** Components are listed on inventory list **USA TSCA INVENTORY** Components are listed on inventory list

Canada

**WHMIS** B-2: Flammable liquid with Flash Point lower than 37.8°C (100°F)

D-2B: Material causing other toxic effects

### **SECTION 16. OTHER INFORMATION**

THIS SUBSTANCE IS A POTENTIAL SENSITISER - ENSURE PRECAUTIONS ARE TAKEN. IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

HMIS Rating (USA): 2 - 4 - 0 - I (Health-Flam-Reactivity-PPE)

## Hazard (H) phrases associated with components

H225: Highly flammable liquid and vapor

H226: Flammable liquid and vapor

H302 : Harmful if swallowed

H304: May be fatal if swallowed and enters airways

H315: Causes skin irritation

H318: Causes serious eye damage H319: Causes serious eye irritation H335: May cause respiratory irritation

H336: May cause drowsiness or dizziness

H400: Very toxic to aquatic life

H410: Very toxic to aquatic life with long lasting effects

#### Abbreviations

Code: Abbreviation: Meaning

: : highly flammable

N: : dangerous for the environment

Xn::harmful

-----: : : Associated pictogram code shown in brackets
H225 : Flam. Liq. 2 : (GHS02) Flammable liquids, Hazard Category 2
H226 : Flam. Liq. 3 : (GHS02) Flammable liquids, Hazard Category 3

H302 : Acute Tox. 4 : (GHS07) Acute toxicity (oral), Hazard Category 4
H304 : Asp. Tox. 1 : (GHS08) Aspiration hazard, Hazard Category 1
H315 : Skin Corr/Irrit. 2 : (GHS07) Skin corrosion/irritation, Hazard Category 2

H318: Eye Dam/Irrit 1: (GHS05) Serious eye damage/eye irritation, Hazard Category 1
H319: Eye Dam/Irrit 2: (GHS07) Serious eye damage/eye irritation, Hazard Category 2
H335: STOT SE 3: (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation
H336: STOT SE 3: (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Narcosis
H400: Aquatic. Acute 1: (GHS09) Hazardous to the aquatic environment ^ Acute Hazard, Category 1
H410: Aquatic Chronic 1: (GHS09) Hazardous to the aquatic environment ^ Chronic Hazard, Category 1

ACGIH: American Conference of Governmental Industrial Hygienist

ATE : Acute Toxicity Estimate

: CAS : Chemical Abstracts Service : CHIP : Chemicals (Hazard Information and Packaging for supply)

CLP: Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

CNS : Central Nervous System
DIN : Standard of the German Institute for Standardization

: DOT : Department of Transport : EC : European Community

EC50: Effective Concentration (Median) for 50% of the response under test

ECB: European Chemicals Bureau ECHA: European Chemicals Agency, Helsinki (http://echa.europa.eu/home\_en.asp)

EEC: European Economic Community

EINECS: European Inventory of Existing Chemical Substances ELINCS: European List of Notified Chemical Substances

GHS: Globally Harmonized System of Classification and Labelling of Chemicals HMIS: Hazardous Materials Information System (USA only)

IATA : International Air Transport Association
IMDG : International Maritime Dangerous Goods Code

IMO : International Maritime Organization

INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007 ISO : International Standards Organization

L.E.L. : Lower explosive limit

: LD50/LC50 : Median (50%) lethal dose/concentration : mg/m3 : Milligrams per cubic meter : MSDS : Material safety data sheet : n/.a. : Not available

NC : No Classification

: No : Number : OEL : Occupational exposure limit

OEL-CL: Occupational exposure limit - control limit
OEL-RL: Occupational exposure limit - recommended limit
OHS Act: Occupational Health and Safety Act

: P statement : Precautionary statement

SDS: ACTIVATOR Date issued: 2/16/2015 Rev. Date: 07/20/2016 Page 5 of 6

```
PEL: Permissible Exposure Limit
PPE: Personal protective equipment
ppm: Parts per million
REACH: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals
RTDG: Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG)
SABS: South African Bureau of Standards
SANS: South African National Standards
SAPMA: South African Paint Manufacturers Association
SARA 313: Toxic Release Inventory Reporting SRA Section 3
SDS: Safety Data Sheet
STOEL: Short-term occupational exposure limit
STOT-RE: Specific Target Organ Toxicity - Repeated Exposure
STOT-SE: Specific Target Organ Toxicity - Single Exposure
TDG: Transport of Dangerous Goods
TSCA: Toxic Substance Control Act (USA only)
TWA: Time weighted average
U.E.L.: Upper explosive limit
UN: United Nations
WHMIB: Workplace Hazardous Materials Information Systems (Canada only)
```

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)
OEL's derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42). All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.

While all information is accurate to the best of our knowledge, we continue updating ALL SDS document formats in accordance with the most recent GHS mandated changes.

(Date of issue: 02/16/2015 Date of Revision: 07/20/2016)

SDS: ACTIVATOR Date issued: 2/16/2015 Rev. Date: 07/20/2016 Page 6 of 6