

SAFETY DATA SHEET

Date issued: 02/16/2015

MONTANA® PS3042 PRIMER / SEALER

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

PS3042 PRIMER / SEALER **Product Code Product Name**

Recommended use A paint or paint constituent product

UNITED STATES OF AMERICA

Manufacturer

ChemSpec USA, Inc. **Company Name**

9287 Smucker Road

Address Orrville, Ohio

44667

1-330-669-8512 Telephone Facsimile 1-330-669-3965

Emergency Contact

Contact Name CHEMTREC **Contact Number** 1-800-424-9300

SECTION 2. HAZARDS IDENTIFICATION

HAZARDOUS MIXTURE, DANGEROUS GOODS

Classification reference SANS10234 (1272/2008/EC) :

Classification of the substance or mixture

(H225)Flammable liquids, Hazard Category 2 Skin corrosion/irritation, Hazard Category 2

(H318) Serious eye damage/eye irritation, Hazard Category 1

(H335) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation

GHS label elements, including precautionary statements

Signal word Danger

Pictograms



Hazard and Precautionary Statements

Hazard Statements

Highly flammable liquid and vapors

Causes skin irritation

Causes serious eye damage

May cause respiratory irritation

Precautionary Statements
Prevention Statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment. – if the explosive is electrostatically sensitive. Use explosion-proof electrical/ventilating/lighting/.../ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash ... thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response Statements

IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Call a POISON CENTER or doctor/physician if you feel unwell.

SDS: PRIMER / SEALER Date issued: 02/16/2015 Rev. Date: 07/20/2016 Page 1 of 6 Specific treatment (see ... on this label). ... Reference to supplemental first aid instruction.

If skin irritation occurs: Get medical advice/ attention.

Take off contaminated clothing and wash before reuse.

In case of fire: Use powder/... for extinction.

Storage Statements

Store in a well-ventilated place. Keep container tightly closed. - if product is volatile so as to generate hazardous atmosphere.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal Statements

Dispose of contents/container in accordance with local/regional/ national/international regulations in accordance with local/regional/ national/international regulation

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Product type : Mixture **Generic name :** PAINT or PAINT RELATED MATERIAL **CAS No. :** Not applicable **EU Index No :** Not applicable **UN No :** 1263

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

EC Labels CAS Number EC Index 4-METHYLPENTAN-4-ONE <20 % 108-10-1 606-004-00-4 F Xn 2-BUTOXYETHANOL <13 % Xn 111-76-2 603-014-00-0 PROPYL ALCOHOL N & 1-OL <5 % F Xi 71-23-8 603-003-00-0 **XYLENE** <12.5 * % 1330-20-7 Xn 601-022-00-9 BUTAN-2-OI <20 * % - Xi 78-92-2 603-127-00-5

Classification reference SANS10234 (1272/2008/EC):

EC Index Classification | Hazard Code |

606-004-00-4 Flam. Liq. 2;Acute Tox. 4 ;Eye Irrit. 2;STOT SE 3 | H225;H332;H319;H335 |

603-014-00-0 Acute Tox. 4 ;Acute Tox. 4 ;Acute Tox. 4 ;Eye Irrit. 2;Skin Irrit. 2 | H332;H312;H302;H319;H315 |

603-003-00-0 Flam. Liq. 2;Eye Dam/Irrit 1;STOT SE 3 | H225;H318;H336 |

601-022-00-9 Flam. Liq. 3;Acute Tox. 4 ;Acute Tox. 4 ;Skin Irrit. 2 | H226;H332;H312;H315 | 603-127-00-5 Flam. Liq. 3;Eye Irrit. 2;STOT SE 3;STOT SE 3 | H226;H319;H335;H336 |

SECTION 4. FIRST AID MEASURES

Inhalation Move to fresh air. In case of discomfort seek medical attention.

Skin Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention

Eyes Rinse well with water and seek medical advice if discomfort persists.

Ingestion Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical advice.

SECTION 5. FIRE FIGHTING MEASURES

Suitable extinguishing media:

Foam. Dry powder. Fog to cool and control. Do NOT use water jets.

Specific hazards arising from the chemical:

Containers can burst in a fire. Can form explosive vapors/air mixture. Static discharge hazard!

Highly flammable with toxic fumes.

Cool containers in case of fire.

Special protective actions for fire-fighters :

Suitable extinguishing media: Foam, dry agent

Substance reacts violently/is explosive

For fires use breathing apparatus. If no fire, breathing apparatus not essential Prevent, by any means available, spillage from entering drains or water courses

SECTION 6. ACCIDENTAL RELEASE MEASURES

Contain & collect. Use an inert - NOT sawdust. Keep out of drains & sewers.

Wear protective equipment (see Section 8). Keep unprotected persons away.

Do not allow product to reach sewage system or any water course.

Remove ignition sources and provide sufficient ventilation

SECTION 7. HANDLING AND STORAGE

Storage:

Store separately from: explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

No open flames. No smoking. No sparks.

Keep containers cool. Avoid free fall of liquid - use earthing.

Subject to local bylaws

Handling

Ensure good ventilation/exhaustion at the workplace

Do not spray on a naked flame or any incandescent material

Eating, drinking and smoking in work areas is prohibited

Wash hands after use

SDS: PRIMER / SEALER Date issued: 02/16/2015 Rev. Date: 07/20/2016 Page 2 of 6

Remove contaminated clothing and protective equipment before entering eating areas

InhalationSkinIn case of insufficient ventilation, use suitable respiratory protection.SkinAvoid direct contact. Use barrier cream and impervious gloves.

Eyes Avoid any form of direct contact. Do not touch eyes with dirty hands or gloves.

Ingestion Observe the rules of hygiene. Wash before eating, drinking or smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

| Name | CAS Number | | TWA OEL | STOEL | STOEL | OEL | Vap.Press. |
|-------------------------|--|--------------|---------|---------|-------|-------|------------|
| PRIMER / SEALER | - Not applicable | (mg/m3) e | (ppm) | (mg/m3) | (ppm) | Туре | (mmHg) |
| Components : | | | | | | | |
| 4-METHYLPENTAN-4-ONE | 108-10-1 | 205 | 50 | 300 | 75 | RL+ S | 16 |
| 2-BUTOXYETHANOL | 111-76-2 | 120 | 25 | | | CL S | .76 |
| PROPYL ALCOHOL N & 1-OL | 71-23-8 | 500. | 200. | 625 | 250 | RL S | 19 |
| XYLENE | 1330-20-7 | 435 | 100 | 650. | 150. | RL+ S | 6.7 |
| BUTAN-2-OL | 78-92-2 | 300 | 100 | 450 | 150 | RL | |
| | (CL/RL = Controlled/Recommended level 'S' = Skin annotation) | | | | | | |

OEL Type: Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary

Appropriate hand protection and protective clothing must always be used

Keep away from foodstuffs, beverages and feed Wash hands before breaks and at the end of work

Paint Type Mixture of synthetic resins, pigments and solvents

General PPE Requirements For Mixing, Brush Application, Roller Application, Pouring, etc.

Personal protective equipment:

Skin PPE: Overall and impervious gloves (e.g. nitrile rubber) **Respiratory PPE**: Air purifying respirator (e.g. cartridge type)

Eye PPE: Face shield or solvent resistant goggles

HMIS Rating (USA) 2 - 4 - 0 - I (Health-Flam-Reactivity-PPE)

SAPMA Rating 2-H-E PPE : Gloves, Respirator and Eye protection



SPRAY BOOTH

Spray booth Type Spray booth complying with National Standards

Skin PPE Nitrile Gloves

Eyes PPE Face shield or solvent resistant goggles

Respiratory Protection Air supplied full face piece or head covering respirator suitable for organic vapors/particulates

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Property Value Appearance Viscous liquid Odor Pungent рН not available Boiling point >35°C Melting point not available Flash point <23°C Explosive prop not available Oxidizing prop not available Vapor pressure not available Density not available Water solubility not available Fat solubility
Partition coefficient not available not available Viscosity not available Vapor density not available Evaporation rate not available Auto ignition temperature not available L.E.L. not available U.E.L. not available % non volatile not available 3.57 lbs./gal (428 g/L) Regulatory VOC Actual VOC 3.57 lbs./gal (428 g/L)

SDS: PRIMER / SEALER Date issued: 02/16/2015 Rev. Date: 07/20/2016 Page 3 of 6

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions

Prone to ignite by static

No reaction with fire-fighting water

Keep away from: explosives, toxic gases, oxidising substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

SECTION 11. TOXICOLOGICAL INFORMATION

LC50 Inhal(gas) **CAS Number** LD50 Oral LD50 Skin LC50 Inhal(mist) Name ma/ka mg/kg Vmaa mg/lt

PRIMER / SEALER Not applicable >500 Components

4-METHYLPENTAN-4-ONE 108-10-1 2080 mg (Rat)

230g 111-76-2 2-BUTOXYETHANOL 1480 mg (Rat)

5040 mg (Rabbit) PROPYL ALCOHOL N & 1-OL 71-23-8 1870 mg (Rat) XYI FNF 1330-20-7

4300 mg (Rat) 5000 mg (Rabbit) **BUTAN-2-OL** 6480 mg (Rat) 78-92-2

Inhalation HARMFUL. Excessive exposure to this material must be avoided.

Skin HARMFUL BY CONTACT.

Irritating - may cause damage if not given prompt attention. Eyes Ingestion Harmful if swallowed. Can affect CNS. Systemic poison.

SECTION 12. ECOLOGICAL INFORMATION

May have short term environmental effects. Contain, monitor & remove No further relevant information available Aquatic toxicity: Persistence and degradability: No further relevant information available. Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available.

Available ecological data of ingredients:

CAS Number Aquatic Toxicity Name

2-BUTOXYETHANOL 111-76-2 LC50 fathead minnow = 1700 mg/l; 96h XYLENE 1330-20-7 LC50 (goldfish) = 13 mg/L; 24 hr LC50 (rainbow trout) = 13.5 mg/L; 96 h

EC50 Daphnia magna 3.82 mg/L, 48 h

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

SECTION 14. TRANSPORT INFORMATION

UN Number 1263

Shipping Name PAINT or PAINT RELATED MATERIAL

IMO Class 3.2 **Packing Group** Ш **Action Code** 127 HazChem 3[Y]E **Kemler Code** 30

USA (DOT) UN1263 CANADA (TDG) UN1263



SECTION 15. REGULATORY INFORMATION

CANADIAN DSL INVENTORY Components are listed on inventory list

USA TSCA INVENTORY Components are listed on inventory list

Canada

WHMIS B-2: Flammable liquid with Flash Point lower than 37.8°C (100°F)

D-2B: Material causing other toxic effects

Date issued: 02/16/2015 PRIMER / SEALER SDS: Rev. Date: 07/20/2016 Page 4 of 6

SECTION 16. OTHER INFORMATION

TWA: Time weighted average U.E.L.: Upper explosive limit UN: United Nations

: WHMIS: Workplace Hazardous Materials Information Systems (Canada only)

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES. IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE. HMIS Rating (USA): 2 - 4 - 0 - I (Health-Flam-Reactivity-PPE)

Hazard (H) phrases associated with components H225: Highly flammable liquid and vapors H226: Flammable liquid and vapors H302: Harmful if swallowed H312: Harmful in contact with skin H315: Causes skin irritation H318: Causes serious eye damage H319: Causes serious eye irritation H332: Harmful if inhaled H335: May cause respiratory irritation H336: May cause drowsiness or dizziness Abbreviations Code: Abbreviation: Meaning -:: flammable F::highly flammable Xi::irritant Xn::harmful : : Associated pictogram code shown in brackets H225 : Flam. Liq. 2 : (GHS02) Flammable liquids, Hazard Category 2 H226 : Flam. Liq. 3 : (GHS02) Flammable liquids, Hazard Category 3 H302 : Acute Tox. 4 : (GHS07) Acute toxicity (oral), Hazard Category 4 H312 : Acute Tox. 4 : (GHS07) Acute toxicity (dermal), Hazard Category 4 H315 : Skin Corr/Irrit. 2 : (GHS07) Skin corrosion/irritation, Hazard Category 2 H318 : Eye Dam/Irrit 1 : (GHS05) Serious eye damage/eye irritation, Hazard Category 1 H319 : Eye Dam/Irrit 2 : (GHS07) Serious eye damage/eye irritation, Hazard Category 2 H332: Acute Tox. 4: (GHS07) Acute toxicity (inhalation), Hazard Category 4 H335: STOT SE 3: (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation H336: STOT SE 3: (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Narcosis ATE: Acute Toxicity Estimate CAS : Chemical Abstracts Service CHIP : Chemicals (Hazard Information and Packaging for supply) CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures CNS: Central Nervous System DIN: Standard of the German Institute for Standardization DOT : Department of Transport EC: European Community EC50: Effective Concentration (Median) for 50% of the response under test ECB : European Chemicals Bureau ECHA : European Chemicals Agency, Helsinki (http://echa.europa.eu/home_en.asp) EEC : European Economic Community EINECS: European Inventory of Existing Chemical Substances ELINCS: European List of Notified Chemical Substances GHS: Globally Harmonized System of Classification and Labelling of Chemicals HMIS: Hazardous Materials Information System (USA only) IATA : International Air Transport Association IMDG: International Maritime Dangerous Goods Code IMO: International Maritime Organization INS: Guidance on Identification and Naming of Substances under REACH, ECHA, 2007 ISO: International Standards Organization L.E.L.: Lower explosive limit LD50/LC50: Median (50%) lethal dose/concentration mg/m3 : Milligrams per cubic meter MSDS : Material safety data sheet n/.a. : Not available NC : No Classification No : Number OEL: Occupational exposure limit : OEL-CL: Occupational exposure limit - control limit : OEL-RL: Occupational exposure limit - recommended limit : OHS Act: Occupational Health and Safety Act P statement : Precautionary statement PEL : Permissible Exposure Limit PPE : Personal protective equipment ppm: Parts per million REACH: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals RTDG: Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG) SABS: South African Bureau of Standards SANS: South African National Standards SAPMA: South African Paint Manufacturers Association SARA 313 : Toxic Release Inventory Reporting SRA Section 3 SDS : Safety Data Sheet STOEL: Short-term occupational exposure limit STOT-RE: Specific Target Organ Toxicity - Repeated Exposure STOT-SE: Specific Target Organ Toxicity - Single Exposure : TDG : Transport of Dangerous Goods : TSCA : Toxic Substance Control Act (USA only)

SDS: PRIMER / SEALER Date issued: 02/16/2015 Rev. Date: 07/20/2016 Page 5 of 6

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)
OEL's derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42). All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.

While all information is accurate to the best of our knowledge, we continue updating ALL SDS document formats in accordance with the most recent GHS mandated changes.

(Date of issue: 02/16/2015 Date of Revision: 07/20/2016)

SDS: PRIMER / SEALER Date issued: 02/16/2015 Rev. Date: 07/20/2016 Page 6 of 6