



SAFETY DATA SHEET

1. Identification

| | | |
|---|--|----------------|
| Product identifier | Radiant VOC Compliant Dressing | |
| Other means of identification | | |
| Product Code | 1342 | |
| Recommended use | Dressing | |
| Recommended restrictions | None known. | |
| Manufacturer/Importer/Supplier/Distributor information | | |
| Manufacturer | | |
| Company name | Presta Products | |
| Address | 361 Fairview Ave Barberton, OH 44203 United States | |
| Telephone | Phone | 800-253-2526 |
| | Fax | 330-777-8317 |
| Website | www.prestaproducts.com | |
| E-mail | msdsinfo@malcopro.com | |
| Contact person | Technical Department | |
| Emergency phone number | Phone | 1-800-424-9300 |

2. Hazard(s) identification

| | | |
|------------------------------|----------------------|------------|
| Physical hazards | Flammable liquids | Category 2 |
| Health hazards | Acute toxicity, oral | Category 5 |
| | Aspiration hazard | Category 1 |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |

Label elements



| | |
|--|---|
| Signal word | Danger |
| Hazard statement | Highly flammable liquid and vapor. May be harmful if swallowed. May be fatal if swallowed and enters airways. |
| Precautionary statement | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/eye protection/face protection. |
| Response | If swallowed: Immediately call a poison center/doctor. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a poison center/doctor if you feel unwell. Do NOT induce vomiting. In case of fire: Use appropriate media to extinguish. |
| Storage | Store in a well-ventilated place. Keep cool. Store locked up. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | Combustible. |
| Supplemental information | None. |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|-----------|
| Distillates (Petroleum), Hydrotreated Light | | 64742-47-8 | 60 - < 70 |
| Ethylene Glycol Monobutylether | | 111-76-2 | 3 - < 5 |
| Other components below reportable levels | | | 30 - < 40 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|---|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists. |
| Eye contact | Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. Direct contact with eyes may cause temporary irritation. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed. |
| General information | Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Alcohol resistant foam. Water fog. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | Combustible. Highly flammable liquid and vapor. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. |

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat and sources of ignition. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value |
|---|------|-----------------------|
| Ethylene Glycol Monobutylether (CAS 111-76-2) | PEL | 240 mg/m ³ |
| | | 50 ppm |

US. ACGIH Threshold Limit Values

| Components | Type | Value |
|---|------|--------|
| Ethylene Glycol Monobutylether (CAS 111-76-2) | TWA | 20 ppm |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|---|------|----------------------|
| Ethylene Glycol Monobutylether (CAS 111-76-2) | TWA | 24 mg/m ³ |
| | | 5 ppm |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|---|----------|--|---------------------|---------------|
| Ethylene Glycol Monobutylether (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | * |

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene Glycol Monobutylether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene Glycol Monobutylether (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene Glycol Monobutylether (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

| | |
|---------------------------------------|---|
| Eye/face protection | Face shield is recommended. Wear safety glasses with side shields (or goggles). |
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. |
| Other | Wear suitable protective clothing. |
| Respiratory protection | If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. |

9. Physical and chemical properties

| | |
|---|-----------------------------|
| Appearance | Clear. |
| Physical state | Liquid. |
| Form | Liquid. |
| Color | Blue |
| Odor | Solvent. |
| Odor threshold | Not available. |
| pH | none |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | Not available. |
| Flash point | 135.0 °F (57.2 °C) |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 0.11 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 460.4 °F (238 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | 10 cP |
| Viscosity temperature | 68 °F (20 °C) |
| Other information | |
| Density | 7.17 lb/gal |
| Explosive properties | Not explosive. |
| Flammability class | Combustible IIIA estimated |
| Oxidizing properties | Not oxidizing. |
| VOC (Weight %) | 3 % by weight |

10. Stability and reactivity

| | |
|---|--|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful. |
| Skin contact | 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | May be harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. |

Symptoms related to the physical, chemical and toxicological characteristics
Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

| Components | Species | Test Results |
|---|------------|------------------|
| Ethylene Glycol Monobutylether (CAS 111-76-2) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 400 mg/kg |
| Inhalation | | |
| LC50 | Mouse | 700 ppm, 7 Hours |
| | Rat | 450 ppm, 4 Hours |
| Oral | | |
| LD50 | Guinea pig | 1.2 g/kg |
| | Mouse | 1.2 g/kg |
| | Rabbit | 0.32 g/kg |
| | Rat | 560 mg/kg |

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene Glycol Monobutylether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

| | |
|---|---|
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | Not classified. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | May be fatal if swallowed and enters airways. |
| Chronic effects | May be harmful if absorbed through skin. Prolonged inhalation may be harmful. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans. |

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | Species | Test Results |
|--|--|---------------------|
| Distillates (Petroleum), Hydrotreated Light (CAS 64742-47-8) | | |
| Aquatic | | |
| Fish | LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 2.9 mg/l, 96 hours |
| Ethylene Glycol Monobutylether (CAS 111-76-2) | | |
| Aquatic | | |
| Fish | LC50 Inland silverside (Menidia beryllina) | 1250 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Ethylene Glycol Monobutylether 0.83

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

| | |
|-------------------------------------|---|
| UN number | UN1993 |
| UN proper shipping name | Flammable Liquids, N.O.S (Contains Petroleum Products) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

IATA

| | |
|-------------------------------------|---|
| UN number | UN1993 |
| UN proper shipping name | Flammable Liquids, N.O.S (Contains Petroleum Products) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | No. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Other information | |
| Passenger and cargo aircraft | Forbidden. |
| Cargo aircraft only | Forbidden. |

IMDG

| | |
|-------------------------------------|---|
| UN number | UN1993 |
| UN proper shipping name | Flammable Liquids, N.O.S (Contains Petroleum Products) |
| Transport hazard class(es) | |
| Class | 3 |
| Subsidiary risk | - |
| Packing group | III |
| Environmental hazards | |
| Marine pollutant | No. |
| EmS | Not available. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

| | |
|--------------------------|------------------------|
| Hazard categories | Immediate Hazard - Yes |
| | Delayed Hazard - No |
| | Fire Hazard - Yes |
| | Pressure Hazard - No |
| | Reactivity Hazard - No |

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylene Glycol Monobutylether (CAS 111-76-2)

US. Massachusetts RTK - Substance List

Ethylene Glycol Monobutylether (CAS 111-76-2)

US. New Jersey Worker and Community Right-to-Know Act

Ethylene Glycol Monobutylether (CAS 111-76-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethylene Glycol Monobutylether (CAS 111-76-2)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|-------------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|-------------------------------|
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 10-29-2014

Revision date 04-22-2016

Version # 08

Disclaimer Malco Automotive cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information Physical & Chemical Properties: Multiple Properties