

## 1 Identification of substance

- **Product details**
- **Trade name:** 39683 Self Etching Primer Gray
- **Article number:** 39683
- **Manufacturer/Supplier:**  
SEM Products, Inc.  
651 Michael Wylie Dr.  
Charlotte, NC 28217  
USA  
(704)522-1006
- **Information department:** 24HR EMERGENCY CHEMTREC 800-424-9300

## 2 Composition/Data on components

- **Chemical characterization**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

68476-86-8	Petroleum gases, liquefied, sweetened	25-50%
67-64-1	acetone	10-25%
110-19-0	isobutyl acetate	2.5-10%
108-88-3	toluene	2.5-10%
141-78-6	ethyl acetate	2.5-10%
78-93-3	butanone	2.5-10%
	MALEIC MODIFIED ROSIN RESIN	2.5-10%
9004-70-0	CELLULOSE NITRATE	2.5-10%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	2.5-10%
123-86-4	n-butyl acetate	≤ 2.5%
67-63-0	propan-2-ol	≤ 2.5%
14808-60-7	Quartz (SiO <sub>2</sub> )	≤ 2.5%
1330-20-7	xylene	≤ 2.5%
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	≤ 2.5%
1330-78-5	tris(methylphenyl) phosphate	≤ 2.5%
84-74-2	dibutyl phthalate	≤ 2.5%

## 3 Hazards identification

- **Hazard description:**



Toxic  
Extremely flammable

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.  
Warning! Pressurized container.  
May cause cancer by inhalation.  
May cause harm to the unborn child.  
Extremely flammable.  
Irritating to eyes.

(Contd. on page 2)

USA

**Trade name: 39683 Self Etching Primer Gray**

(Contd. of page 1)

*Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.*

*Possible risk of harm to the unborn child.*

*Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.*

*85.4 % by mass of the contents are flammable*

*Keep out of the reach of children.*

· **Classification system:**

*The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.*

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 4

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*2

Fire = 4

Reactivity = 0

#### 4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

#### 5 Fire fighting measures

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Wear self-contained respiratory protective device.

#### 6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

USA

(Contd. on page 3)



**Trade name: 39683 Self Etching Primer Gray**

(Contd. of page 2)

## 7 Handling and storage

- **Handling:**
- **Information for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Store away from oxidizing agents.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Do not gas tight seal receptacle.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

## 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

### 68476-86-8 Petroleum gases, liquefied, sweetened

TLV Short-term value: 2950 mg/m<sup>3</sup>, 1000 ppm

### 67-64-1 acetone

PEL 2400 mg/m<sup>3</sup>, 1000 ppm  
REL 590 mg/m<sup>3</sup>, 250 ppm  
TLV Short-term value: 1782 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1188 mg/m<sup>3</sup>, 500 ppm  
BEI

### 110-19-0 isobutyl acetate

PEL 700 mg/m<sup>3</sup>, 150 ppm  
REL 700 mg/m<sup>3</sup>, 150 ppm  
TLV 713 mg/m<sup>3</sup>, 150 ppm

### 108-88-3 toluene

PEL Short-term value: C 300; 500\* ppm  
Long-term value: 200 ppm  
\*10-min peak per 8-hr shift  
REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
TLV 188 mg/m<sup>3</sup>, 50 ppm  
Skin; BEI

(Contd. on page 4)



**Trade name: 39683 Self Etching Primer Gray**

(Contd. of page 3)

<b>141-78-6 ethyl acetate</b>	
PEL	1400 mg/m <sup>3</sup> , 400 ppm
REL	1400 mg/m <sup>3</sup> , 400 ppm
TLV	1440 mg/m <sup>3</sup> , 400 ppm
<b>78-93-3 butanone</b>	
PEL	590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm BEI
<b>123-86-4 n-butyl acetate</b>	
PEL	710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 713 mg/m <sup>3</sup> , 150 ppm
<b>67-63-0 propan-2-ol</b>	
PEL	980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm
<b>14808-60-7 Quartz (SiO<sub>2</sub>)</b>	
REL	0.05* mg/m <sup>3</sup> *Respirable dust
TLV	(0.05 R) mg/m <sup>3</sup> NIC-0.025 R
<b>1330-20-7 xylene</b>	
PEL	435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm (o-, m-, & p-isomers)
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
<b>84-74-2 dibutyl phthalate</b>	
PEL	5 mg/m <sup>3</sup>
REL	5 mg/m <sup>3</sup>
TLV	5 mg/m <sup>3</sup>

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

(Contd. on page 5)

**Trade name: 39683 Self Etching Primer Gray**

(Contd. of page 4)

· **Breathing equipment:**

*In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.*

· **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

· **Material of gloves**

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **General Information**

<b>Form:</b>	Aerosol
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic

· **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** < -17°C (< 1°F)

· **Flash point:** < -17°C (< 1°F)

· **Ignition temperature:** 405.0°C (761°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:**

· **Explosion limits:**  
**Lower:** 1.9 Vol %  
**Upper:** 13.0 Vol %

· **Vapor pressure at 20°C (68°F):** 233.0 hPa (175 mm Hg)

· **Density at 20°C (68°F):** 0.78 g/cm<sup>3</sup>

· **Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

· **Solvent content:**

**Organic solvents:** 82.5 %

(Contd. on page 6)

Trade name: 39683 Self Etching Primer Gray

(Contd. of page 5)

VOC content: 59.3 %  
489.2 g/l / 4.08 lb/gl

· Solids content: 14.6 %

### 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:**  
Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)  
Hydrocarbons

### 11 Toxicological information

- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

#### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

#### 84-74-2 dibutyl phthalate

Oral	LD50	8000 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
Carcinogenic if inhaled.

### 12 Ecological information

- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.

### 13 Disposal considerations

- **Product:**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

Trade name: 39683 Self Etching Primer Gray

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

· **DOT regulations:**



- **Hazard class:** 2.1
- **Identification number:** UN1950
- **Packing group:** -
- **Proper shipping name (technical name):** AEROSOLS, flammable
- **Label:** 2.1

· **Land transport ADR/RID (cross-border):**



- **ADR/RID class:** 2 5F Gases
- **Danger code (Kemler):** 23
- **UN-Number:** 1950
- **Packaging group:** -
- **Label:** 2.1
- **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



- **IMDG Class:** 2.1
- **UN Number:** 1950
- **Label:** 2.1
- **Packaging group:** -
- **EMS Number:** F-D,S-U
- **Marine pollutant:** No
- **Propper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 2.1
- **UN/ID Number:** 1950
- **Label:** 2.1
- **Packaging group:** -

(Contd. on page 8)



**Trade name: 39683 Self Etching Primer Gray**

(Contd. of page 7)

**Propper shipping name:** AEROSOLS, flammable

**15 Regulations**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3	toluene
78-93-3	butanone
67-63-0	propan-2-ol
1330-20-7	xylene
14807-96-6	Talc (Mg3H2(SiO3)4)
84-74-2	dibutyl phthalate
67-56-1	methanol
	ACRYLIC RESIN
100-41-4	ethylbenzene

· **TSCA (Toxic Substances Control Act):**

68476-86-8	Petroleum gases, liquefied, sweetened
67-64-1	acetone
110-19-0	isobutyl acetate
108-88-3	toluene
141-78-6	ethyl acetate
78-93-3	butanone
13463-67-7	titanium dioxide
64742-94-5	Solvent naphtha (petroleum), heavy arom.
123-86-4	n-butyl acetate
67-63-0	propan-2-ol
14808-60-7	Quartz (SiO2)
1330-20-7	xylene
14807-96-6	Talc (Mg3H2(SiO3)4)
1330-78-5	tris(methylphenyl) phosphate
84-74-2	dibutyl phthalate

· **Proposition 65**

· **Chemicals known to cause cancer:**

14808-60-7	Quartz (SiO2)
1330-20-7	xylene
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
1333-86-4	Carbon black

· **Chemicals known to cause reproductive toxicity:**

108-88-3	toluene
----------	---------

(Contd. on page 9)





**Trade name: 39683 Self Etching Primer Gray**

(Contd. of page 8)

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	D
108-88-3	toluene	D
78-93-3	butanone	D
1330-20-7	xylene	D
84-74-2	dibutyl phthalate	D
100-41-4	ethylbenzene	D

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
13463-67-7	titanium dioxide	3
67-63-0	propan-2-ol	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
1330-20-7	xylene	3
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	TRACE AMOUNTS OF 14808-60-7
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
13463-67-7	titanium dioxide	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
1330-20-7	xylene	A4
14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	A4
1333-86-4	Carbon black	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO <sub>2</sub> )
1333-86-4	Carbon black

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Toxic  
Extremely flammable

· **Hazard-determining components of labelling:**

tris(methylphenyl) phosphate  
toluene  
dibutyl phthalate

(Contd. on page 10)

**Trade name: 39683 Self Etching Primer Gray**

(Contd. of page 9)

Quartz (SiO<sub>2</sub>)

· **Risk phrases:**

*May cause cancer by inhalation.*

*May cause harm to the unborn child.*

*Extremely flammable.*

*Irritating to eyes.*

*Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.*

*Possible risk of harm to the unborn child.*

· **Safety phrases:**

*Avoid exposure - obtain special instructions before use.*

*Keep locked up and out of the reach of children.*

*Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.*

*Wear suitable protective clothing and gloves.*

*In case of insufficient ventilation, wear suitable respiratory equipment.*

· **Special labeling of certain preparations:**

*Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.*

*85.4 % by mass of the contents are flammable*

*Keep out of the reach of children.*

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Mr. George Wallace