# **3M Automotive Aftermarket Division** Coatings





#### **3M Rocker Panel Coating Grey**

3M<sup>TM</sup> Rocker Panel Coating produces a textured finish which resists chipping, abrasion, rusting and weathering. Specifically developed to match OEM medium to coarse textures and produces a resilient under-the-paint coating to protect your vehicle year after year. Ideal for use on rocker panels, under bumpers and under-carriages to prevent exterior corrosion. 3M<sup>TM</sup> Rocker Panel Coating is fast drying, paintable, and offers excellent sound deadening properties. VOC Compliant in all 50 states.

#### **Features and Benefits**

- VOC Compliant in all 50 states
- Medium to coarse texture
- Paintable
- Formulated to match OEM coating
- Color Grey



08889\_sell\_sheet.indd 1 6/27/11 9:08 AM

## **3M Rocker Panel Coating Grey**



### **Direction for Use**



## **Surface Preparation**

Prime all bare metal surfaces with urethane or epoxy primer. Sand the primer using grade P320 - P500, clean the surface and mask accordingly

NOTE 1: When repairing into factory applied chip guard coatings prime the sanded factory coating with epoxy primer to prevent "lifting" or "blistering".

NOTE 2: Apply only to surfaces primed with a 2K urethane, 2K epoxy primer, or clean, sanded paint. Acid etch primers should never be in direct contact with the coating.



## Application And Sanding

Use at temperatures above 65°F (19°C), shake until agitator ball moves freely in the can.

Apply a light even coat to the surface from a distance of 10 - 12 inches (25 - 30 cm). Allow 5 minutes dry time before applying additional coats.

Apply additional coats to match desired texture, allowing adequate dry time between coats to avoid solvent bubbling. Texture can be varied by adjusting application speed, distance, and coating thickness. For best results, invert the can and spray to clear the actuator between coats and after use.



#### **Finishing**

Allow 1 hour dry time when 2 coats are applied (more dry time is needed if additional coats have been applied) prior to painting. Lightly scuff sand using grade P500 - P600 abrasive and apply top coats or primer/sealer (refer to paint manufacturers guidelines for paint application information).

#### **VOC Information**

VOC Compliant in all 50 states.

Please consult state and local regulations. CARB Category: Automotive Bumper and Trim Product. VOC Limit = 1.75 g O3/g product. This product: 1.63 g O3/g product.

#### **Related Products**

Part No	Name/Description	Size	Case Qty
05910	3M™ Rocker Panel Spray - Tan	18 oz	12
05911	3M™ Rocker Panel Spray - Clear	18 oz	12
08964	3M <sup>™</sup> No Cleanup High Coverage Body Schutz <sup>™</sup>	22 fl oz	6
08949	3M <sup>™</sup> No Cleanup Rocker Gard <sup>™</sup> Coating	22 fl oz	6
08804	3M <sup>™</sup> No Cleanup Waterbased Undercoating	18.5 fl oz	6













3M Automotive Aftermarket Division

3M Center Bldg 223-6N-01 St. Paul, MN 55144-1000 U.S.A.

1-877-MMM-CARS (666-2277) or 3MCollision.com Please recycle. Printed in U.S.A.

Please recycle. Printed in U.S.A.

© 3M 2011. All rights reserved.

3M is a trademark of 3M Company.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically sated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product.3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

0888\_sell\_sheet.indd 2 6/27/11 9:10 AM