



UNDERCOATINGS

TECHNICAL DATA SHEET

Description

39463 UNDERCOATING and **40463 LOW VOC UNDERCOATING** are non-paintable, asphalt based products that provide sound-deadening properties, excellent chip resistance and outstanding corrosion protection. **40463** is less than 40% VOC.

Features

- Asphalt based
- Sound-deadening properties
- Chip resistant
- Corrosion protection

Typical Properties

Container	24 oz. aerosol
Color	Black
VOC 39463	3.42 #/gl (410.4 g/l)
VOC 40463	2.57 #/gl (308.2 g/l)
Paintable	No

Handling and Application

PREPARATION: Clean surface with **3837() SEM SOLVE**. Remove any loose paint, rust, oil and grease. Blow off and clean again with **3837()**.



APPLICATION:

Distance:	8-12"
Coats:	2-3 medium wet
Flash time:	3-5 minutes



STORAGE: **39463 UNDERCOATING** and **40463 LOW VOC UNDERCOATING** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **39463** and **40463** is 2 years when stored under normal conditions.



Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

SEM Products, Inc.
651 Michael Wylie Drive Charlotte, NC 28217
Tel: 800/ 831-1122
Fax: 704/ 522-7008
www.sem.ws



RUBBERIZED UNDERCOATINGS

TECHNICAL DATA SHEET

Description

39523 RUBBERIZED UNDERCOATING and **40523 LOW VOC RUBBERIZED UNDERCOATING** are paintable, fast-drying, asphalt free coatings for rust proofing, sound deadening, chip resistance and corrosion protection. **40523** is less than 40% VOC.

Features

- Asphalt free
- Paintable
- Sound-deadening properties
- Fast-drying
- Chip resistant
- Corrosion protection

Typical Properties

Container	24 oz. aerosol
Color	Black
VOC 39523	4.84 #/g1 (580.8 g/l)
VOC 40523	2.79 #/g1 (334.2 g/l)
Paintable	Yes

Handling and Application

PREPARATION: Clean surface with **3837() SEM SOLVE**. Remove any loose paint, rust, oil and grease. Blow off and clean again with **3837()**.



APPLICATION:

Distance:	6-8"
Coats:	2-3 medium wet
Flash time:	3-5 minutes



STORAGE: **39523 RUBBERIZED UNDERCOATING** and **40523 LOW VOC RUBBERIZED UNDERCOATING** should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **39523** and **40523** is 2 years when stored under normal conditions.



Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

SEM Products, Inc.
651 Michael Wylie Drive Charlotte, NC 28217
Tel: 800/ 831-1122
Fax: 704/ 522-7008
www.sem.ws