



EZ COAT

TECHNICAL DATA SHEET

Description

EZ COAT is a direct to metal coating designed to match the color and gloss of factory primer and e-coat colors. It is a quick and easy way to touch up the engine compartments, support rails and trunk areas. If needed, **EZ COAT** can be painted.

Features

- Direct to metal and aluminum
- Quick curing and hiding
- Available in 4 popular OEM colors
- Excellent color and gloss match
- Paintable with most automotive basecoats

Typical Properties

Container
Colors

Aerosol – 16 fl oz

62213 BLACK, 62223 OLIVE GREEN, 62233 LIGHT GREEN and 62243 GRAY

VOC less exempts

600 g/l

MIR

1.5

Coverage

13 ft² per can @ 1 mils DFT

Recommended coats

2-3 coats

Topcoat time

15 minutes

Handling and Application

PREPARATION:



Clean surface thoroughly with **3837() SEM SOLVE** or **38381 WORLD CLASS™ SURFACE CLEANER**. Next, sand with 320 grit paper and re-clean with **3837()** or **38381**.

APPLICATION:



Coats: 2-3 medium coats
Flash time: 5-10 minutes between coats
Dry time: 30 min

NOTE: If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button on top of can and spray with button pointed away from you.

NOTE: After each use, turn can upside down and spray several seconds to clear spray tip.

STORAGE:



EZ COAT should be stored in a cool dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **EZ COAT** is 5 years when stored under normal conditions.

TECHNICAL CONSULTATION SERVICE

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and Friday 8:00 am until 4:30 pm EST.

DISCLAIMER: The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Material Safety Data Sheet (MSDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the MSDS and product label are available upon request.

SEM Products, Inc.
1685 Overview Dr. Rock Hill SC 29730
Tel: 800-831-1122
www.semproducts.com