

# HIGH #5 – Beige, Gray, Dark Gray & White

## Ready to Use High Build Primer

### **ALL HIGH#5 COLOURS AVAILABLE IN 2.1 VOC COMPLIANT**

_					
Des	cri	D	Ш	O	n

**HIGH #5** is a ready to use high build primer/filler in an aerosol. It is used for priming uneven surfaces before top coating.

**High #5** is capable of producing a coating of a film thickness similar to that of a spray gun applied primer. The convenience of using a high build primer in an aerosol means that masking is kept to a minimum. Mixing paint and cleaning spray equipment are avoided as a result of using **HIGH #5** leading to savings in time and materials.

**HIGH #5** is cromate free and easy to sand.

#### **Health and Safety Statement**

FOR PROFESSIONAL USE ONLY. Read full instructions before use.

IMPORTANT: This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the material safety data sheet for full handling instructions and personal protection information. These are available via your local stockist or via the U-POL website at <a href="https://www.u-POL.COM"><u>WWW.U-POL.COM</u></a>. U-POL disclaim any liability where the user does not wear the recommended personal protective equipment.

# Surface preparation and instructions for use

HIGH #5 can be applied to the following surfaces:-

- Fully cured paint.
- Polyester bodyfillers and F.R.P.

Thoroughly clean and degrease surfaces with a suitable panel wipe or thinner. Abrade wet or dry with 280-320 grit abrasive, re-clean, dry and degrease.

#### **Application**

Shake can thoroughly before use for a minimum of 2 minutes.

Apply 1-2 light even coats.

Allow 5-10 minutes flash off time between coats.

#### **Drying time**

Allow 60 minutes before sanding & overcoating.

Drying time is dependent upon film thickness, humidity and temperature.

#### **Over-painting**

**HIGH #5** should be flatted wet with 600-800 grit or dry with 400-600 grit abrasive.

**HIGH #5** may be over-painted with most paint systems.

#### **VOC Information**

MIR Ref. ABP:MIR1.55

#### **Product code**

ALL Aerosols are 450 ml.

UP0783 – (Beige) UP0791 – (Gray) UP0763 – (White) UP0765 – (Dark Gray)

UP0783V - (Beige) 2.1 VOC Compliant
UP0791V - (Gray) 2.1 VOC Compliant
UP0765V - (Dark Gray) 2.1 VOC Compliant
UP0763V - (White) 2.1 VOC Compliant

U-POL US, Inc., 630 Selvaggio Dr, Suite 300, Nazareth, PA 18064 Tel: (800) 340 7824: Fax: (800) 787 5150

Email: sales-us@u-pol.com Website: www.u-pol.com