




ACRYLIC URETHANE SINGLE-STAGE COATINGS

# INTERMIX SYSTEM

A spectrum of colors at a price that makes sense



**2.8 VOC  
MIX RATIO**

4 PARTS PAINT: 1 PART #729 CATALYST  
1 PART #730 REDUCER or quality grade  
LOW VOC urethane reducer

## ADVANTAGE Intermix System

A high solids 2.8 VOC performance acrylic urethane coating designed for fast dry, high gloss and long term color and gloss retention. Available in three mix bases to allow custom tinting using the ADVANTAGE colorant systems.

**MIX AND MATCH  
ENDLESS  
COLORS!**



**COLOR DECK AVAILABLE  
#ADVDECK13**

## 2.8 VOC Product Properties:

- 2.8 LBS PER GALLON (2.8 VOC RTS)  
VOC COMPLIANT COAST TO COAST AND CANADA
- 4:1:1 MIX RATIO
- DIRECT TO METAL
- 320 SQ. FT. PER GALLON @ 3.0 MILS DRY
- 50% + SOLIDS
- HIGH GLOSS
- 30 MINUTE DRY TO TOUCH
- POT LIFE - 8 HOURS
- TO DELIVER - 24 HOURS

**D.T.M.  
DIRECT  
TO METAL**

Call 1-87REFINISH (1-877-334-6474) to find your local ADVANTAGE Refinish Products supplier. Or visit our website: [www.advantagerefinish.com](http://www.advantagerefinish.com) - MSDS/TDS/Flyers  
©2013 Part #760-790 Series, #729, #730 - Intermix System

Autobody Brands International  
a division of IAMG - Scottsdale, Arizona  
To access color formulas:  
[www.advantageintermix.com](http://www.advantageintermix.com)