

PRODUCT FEATURES & APPLICATION



Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

ONE STEP – SELF ETCHING PRIMER

Stock SEP Part 24008
340 g / 16 Oz. Aerosol

Description:

One Step is unique and convenient to use ‘etch type’ primer that provides excellent adhesion for additional top coats, primers, and sealers to metals. This product is compatible with all primer surfacers for spot repair and refinishing. Apply to steel, aluminum, and most metals.

Features:

- Fast drying.
- Excellent sanding, if necessary.
- Strong adhesion to metals, and other substrates.
- Superior adhesion of primer surfacers and other topcoats to product.
- Good filling characteristics.

Touch Dry and Paintable 10 – 20 minutes

Full Cure 30 min – 1 Hour

Application Instructions:

1. Surface should be free of rust and scale.
2. Clean area to be primed with Sure Solve (BSS) or Future Clean (BFC) removing all wax, grease, silicones, and contaminates.
3. Feather edge (sand) original finish. Do not use over fresh paint.
4. Vigorously shake can for 1 minute agitating material.
5. Apply 2-3 even coats holding can 10 - 15 inches from surface.
6. Material can be topcoated and/or sanded within 2 hours. This is important for maximum adhesion of primer to substrate.

Note: Avoid applying any materials on or near catalytic converters, mufflers due to extreme heat.

In the event the MSDS (Material Safety Data Sheet) on this product is not in your files, you can request one from Dominion Sure Seal Regulatory Compliance at 1800 265-0790, ext. MSDS.

Call 1-800-265-0790 or visit us on the web www.dominionsureseal.com

SEP_2_2002