

PRODUCT FEATURES & APPLICATION

Dominion Sure Seal Ltd.

6175 Danville Road, Mississauga, Ontario, Canada L5T 2H7

TEL (905) 670-5411

FAX (905) 670-5174

Hippo Liner Truck Bedliner

Stock **BHBL, Part 100000 - 1.7 litre**
(0.45 gal)

Description: Dominion Sure Seal's latest innovation with this revolutionary new Urethane ~~paste based~~ **Color: Black** protective coating. Ideally suited for applications to Truck Beds (replaces drop-in plastic liners), Trailers, Hoppers, Boats, Off-Road Vehicles, RV's and almost anything that requires space-age durability at a Down-to-Earth price. This rugged coating not only looks good but it protects surfaces against a wide range of extreme conditions and extends truck-box longevity.

Features:

- Easily applied by brush, roller or standard "undercoat" style pneumatic applicator.
- Low aromatic solvents mean low vapour odour when applying.
- Ultra chemical resistant.
- Excellent adhesion to metals, wood, fiberglass, concrete and plastic.
- Remains permanently flexible.
- Seals surfaces against moisture and corrosion.
- Greatly increases resale value of vehicles
- Incredible wear & tear resistance.
- Easily mixed by hand or machine.
- Superior High-Gloss finish.
- Variable film build for many different applications.

WARNING: DO NOT SPRAY (rolling, brushing is ok) IF HUMIDITY EXCEEDS 60%

Surface Preparation:

1. Surface to be coated must be cleaned with silicone & grease remover
2. Loose paint / rust should be removed and affected areas primed
3. Scuff / Sand area with 80-120 grit sandpaper, blow off and wipe clean
4. Mask all area surrounding application area. ****complete application instructions printed on packaging.**

Application:

**limit mixed material to ONE mixed Quart which can be applied within 30 minutes from mixing*

1. Pour ½ contents of Parts A & B into mixing container
2. Mix vigorously for 2 – 3 minutes.
3. Immediately after mixing, apply:

A) -with a natural or synthetic brush in even strokes until sufficient coverage is attained.

B) -using a 3/8 – ½ inch pile synthetic roller sleeve. Apply even coats until desired finish is achieved.

C) -pour mixed contents into "shutz" style can, attach pneumatic applicator Stock BUPA (or equivalent) and @ +50 PSI spray light coats until coverage is uniform.

**** Repeat steps 1 – 3 until surface is completely covered. Allow sufficient flash-off times between coats****

Recommended thickness is 10-12 mils in one coat. If applied to thick in one coat solvent pop or blistering can occur.

Typical Properties Of Hippo Liner

Dry Time: 3 hours @ 70 F

Cure Time: 24 hours @ 70 F = light duty
72 hours @ 70 F = full cure

Additional Information For Hippo Liner

Shelf Life: 12 months at 20 C / 72 F

Practical Coverage: 75 sq. ft. per gallon at 10ml
40 - 50 sq. ft. per 1.7 litre kit.

Normal operating temperature: -20° to 150° F.

Note: Avoid applying any materials on or near catalytic converters, mufflers due to extreme heat.

In the event the MSDS (Material Safety Data Sheet) on this product is not in your files, you can request one from Dominion Sure Seal Regulatory Compliance at 1800 265-0790, ext. MSDS.

BHBL 3_2005