



## SUPER CUT COMPOUND COMPOUNDS

### DESCRIPTION:

**Super Cut Compound** is an aggressive cutting compound designed to remove heavy sanding scratches and oxidation from gel coated surfaces, marbled surfaces and some paints. When used with a 100% twisted wool pad, Super Cut Compound works fast and leaves a high-gloss finish.

### DIRECTIONS:

Shake well before using. Apply a 1" (25 mm) dap of **Super Cut Compound** for a 15" x 18" (.46m x .46m) section and spread with the cutting pad. Buff at 1800-2200 rpm working the buffer slowly from side to side and front to rear, until most of the product is gone and gloss appears. Always ensure finishing strokes are front to back. Repeat as necessary until scratches are removed. Wipe surface clean with a Presta Micro Fiber Cloth, #800135.

### FEATURES & BENEFITS:

- Easily removes 600 grit and finer sanding scratches
- Works fast and leaves a high-gloss finish
- Great for restoring gel coats and marbled surfaces
- Performs exceptionally on marine applications

### RECOMMENDED PAD:

For best results, use our white wool compounding pad, Part# 890141

### PACKAGE SIZES:

Quarts	Part # 134532
Gallons	Part # 134501

T  
E  
C  
H  
D  
A  
T  
A