

DESCRIPTION

MultiMax is a multi-purpose aerosol enamel for exterior or interior use on metal, wood, fiberglass and rigid plastic.

FEATURES

- Outstanding coverage
- Excellent filling properties
- Durable, fast drying finish
- Great adhesion
- Professional finish

SUITABLE SUBSTRATES

- Metal
- Wood
- Fiberglass
- Rigid plastic

TYPICAL PROPERTIES

Part:	Product Name:	Color:	Container:
61013	MultiMax	Flat Black	16 oz. Aerosol
61023	MultiMax	Semi-Gloss Black	16 oz. Aerosol
61033	MultiMax	Gloss Black	16 oz. Aerosol
61043	MultiMax	Aluminum	16 oz. Aerosol
61073	MultiMax	Clear	16 oz. Aerosol
61083	MultiMax	Red Oxide Primer	16 oz. Aerosol
61093	MultiMax	Gloss White	16 oz. Aerosol
61103	MultiMax	Gray Primer	16 oz. Aerosol
61113	MultiMax	Chassis Gray	16 oz. Aerosol

Regulatory VOC:	4.45-4.75 #/gal (535-570 g/L)
Actual VOC:	3.63-4.58 #/gal (436-550 g/L)
MIR 61023, 61033, 61043, 61113, 61093:	< 1.4
Category 61023, 61033, 61043, 61113, 61093:	NFP
MIR/Category 61013:	< 1.2 FCP
MIR/Category 61073:	< 1.1 CCP
MIR/Category 61083, 61103:	< 1.2 PCP



Check local VOC regulations to ensure compliance of all products in your area.

Check local VOC regulations to ensure compliance of all products in your area.

HANDLING AND APPLICATION



PREPARATION:

1. Clean surface thoroughly and dry.
2. Sand surface with 220-320 grit sandpaper.
3. Blow or wipe off dust and re-clean.



MIXING:

Agitate thoroughly! Shake can vigorously for one minute after mixing ball rattles to ensure color uniformity and to prevent clogging. For best results, use only when can temperature is approximately 70°F (21°C).



APPLICATION:

1. Prime any bare metal with **MultiMax Primer**.
2. Mask adjacent areas to protect from overspray
3. If priming, sand with 320 grit sandpaper. Allow primer to dry 30 minutes before top coating with **MultiMax**.
4. If not priming, test a small area for compatibility.
5. Apply light “mist” coats, allowing 5-10 minutes between coats.
6. If applying **MultiMax Clear**, allow **MultiMax** to dry 3 hours before clear coating.

Note: If clogging develops, remove spray button with a twisting motion and clean with material compliant with VOC regulations in your area. Do not stick pin or other object into can. Gently replace spray button with top of can and spray button pointed away from you.



After each use, turn can upside down and spray several seconds to clear spray tip.



STORAGE:

MultiMax should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for **MultiMax** is 3 years when stored under normal conditions.



Check local VOC regulations to ensure compliance of all products in your area.

Technical Consultation Service

Our Technical Staff is ready to assist you with any questions. You are invited to take advantage of our extensive experience, laboratory services and trained field service representatives. Call (800) 831-1122 for answers to your questions. Hours of operation are Monday through Thursday 8:00 am until 5:00 pm EST and on Friday 8:00 am until 4:30 pm EST.

Disclaimer:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as SEM deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label for the material to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material. Copies of the SDS and product label are available upon request.