

Distributed in North America by:

**Peter Kwasny Inc.**

a subsidiary of Peter Kwasny GmbH, Gundelsheim Germany

400 Oser Ave, Suite 1650, Hauppauge, NY11788

1-844-426-6330 Toll free North America


www.spraymax.com

## 1K SPOT BLENDER

Prod.no. 368 0093

### TECHNOLOGY

SprayMax®



- Spray pattern like a spray gun
- High productivity
- Easy application
- Constant atomization pressure during the total application process
- Finest aerosol dispersion
- Professional paint result

### PRODUCT

- Ideal product for spot repair and blend-in jobs
- Easy and time-saving application
- Especially suited for clear over base systems and 2K topcoats
- Very good re dissolving capacity
- Easy to polish
- Provides seamless blend-in-areas

Basis of raw material:

Combination of special resins and solvents

EPA Coating Category

CCP Clear Coatings Product  
PWR Limit 1.50


CARB Aerosol Rule Coating Category (01/2017)

UFC Uniform Finishing Coating  
PWR Limit 1.30

## FIELD OF APPLICATION


Recommended for: spot repair and blend-in-jobs


Substrate: 2K clear coats and 2K topcoats


Pre-Treatment:  The old paintwork within the blend-in area should thoroughly be topped off using a P 2000 – P 4000 grit sand paper

## PROCESSING

Protections:  Personal protection is required respirator mask type A2/P2

 Protective gloves, e.g. from latex or nitrile

Spray passes  Apply several light spray passes to the edge of the blend-in-area immediately after application of the 2K clear coat or 2K topcoat to achieve a smooth transition.

Finish:  When work is finished, reverse aerosol and spray valve empty

Disposal: The emptied aerosols are suitable for household collection.

## CHARACTERISTICS

Solid content: 4.8 % per weight related to active ingredient

Coverage: approx. 5.4 sq ft (0.5 m<sup>2</sup>) /aerosol can

Degree of gloss: n/a

Shelf life: 60 months / 70 °F (20 °C)

Remarks For professional use only

SprayMax® is a registered trade mark of the Peter Kwasny Group.

The information contained in this paper corresponds to our present knowledge and is a guide to our products and their uses. It is not to be understood as a guarantee for certain properties of our products or of their specific applications. The warnings printed on our labels must be respected. Any industrial property rights should be observed.