

Primer/Filler

1K - 3 in 1 Primer Shade

3680 403/404/405

Recommended for repairing small damaged areas / spot repairs and painting parts, as an anti-corrosion primer or primer surfacer. Suitable surfaces: Steel, galvanized steel, aluminum, GRP, hardened old paint, spare part primer, polyester surfaces. (Do not coat with polyester or EP-products).

Article Number

368 0403	368 0404	368 0405
white (423 g /	gray (423 g /	black (423 g /
14.9 oz)	14.9 oz.)	14.9 oz.)

Advantages

- > Great Adhesion to: Plastic (no adhesion promoter required) Aluminum Metal
- > High Film build / Easy to sand / Fast drying
- > Available in three colors to ensure maximum hiding of the basecoat
- > Can be top coated with all paint technologies

3 in 1 Primer Shade Gray 368 0404 Apprêt ton gris 3 dans 1 3 en 1 Primer tono gris AFLAMMABLE/MUY INFLAMABLE - CONTENTS UNDE PRESSURE/CONTENU SOUS PRESSION/EL CONTENU ESTÁ BAJO PRESIÓN FOR HARMFUL/VAPEUR NOCIVE/VAPOR NOCIVO - IRRITANT/FREE

Application Notes



Shake can thoroughly for 1-2 minutes



Apply first coat adjust variator, perform a test spray, apply



Allow to flash 5-10 min. between 2-3 coats



Sand wet or dry (manually) P400 - P500



Primer/Filler

1K - 3 in 1 Primer Shade

3680 403/404/405

Recommended for repairing small damaged areas / spot repairs and painting parts, as an anti-corrosion primer or primer surfacer. Suitable surfaces: Steel, galvanized steel, aluminum, GRP, hardened old paint, spare part primer, polyester surfaces. (Do not coat with polyester or EP-products).

Article Number

368 0403	368 0404	368 0405
white (423 g /	gray (423 g /	black (423 g /
14.9 oz)	14.9 oz)	14.9 oz)

Advantages

- > Great Adhesion to: Plastic (no adhesion promoter required) Aluminum Metal
- > High Film build / Easy to sand / Fast drying
- > Available in three colors to ensure maximum hiding of the basecoat
- > Can be top coated with all paint technologies

3 in 1 Primer Shade Gray 368 0404 Apprêt ton gris 3 dans 1 3 en 1 Primer tono gris AFLAMMABLE/MUY INFLAMABLE - CONTENTS UNDE PRESSURE/CONTENU SOUS PRESSION/EL CONTENU **ESTÁ BAJO PRESIÓN** FOR HARMFUL/VAPEUR NOCIVE/VAPOR NOCIVO - IRRITANT/FREE

Application Notes



Skake can thoroughly for 1-2 min



Apply first coat adjust variator, perform a test spray, apply



Allow to flash 5-10 min between 2-3 coats



Sand wet or dry (manually) P400 - P500