



DRIVING SURFACE PERFECTION™

TECHNICAL DATA SHEET

WIPE#6

SOLVENT BASED DEGREASER AEROSOL



DESCRIPTION

An anti-static, anti-silicone degreaser that removes contaminants including wax, grease and silicones. Easily remove contaminants like road tar, sticky adhesive residue and bugs. Wipes clean without leaving surface residue.

- Fast evaporating for localized repairs
- Formulated to avoid attack on existing paint films, especially those sensitive to solvents. Suggest limited exposure over sanded SMC / Fiberglass, TPO, EDPM and PPP plastics.
- Suitable for removing contaminants on all automotive substrates and existing paint surfaces

APPLICATION GUIDE



Mixing

Shake the aerosol can for at least 2 minutes before use.



Application

- Apply generously to the area to be coated.
- While the panel is still wet, wipe with a clean dry cloth until the degreaser has been completely removed.

STORAGE & VOC INFORMATION



Shelf Life

4 years subject to proper storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry well ventilated area and away from direct sunlight and frost. To maximize the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use to clear the nozzle. If the nozzle becomes blocked, remove it from the can and soak it in gentle thinners.

Recommended Storage Temperature 41°F - 77°F

Recommended Application Temperature 68°F



VOC Information

Order Code	Format	Color	MIR
UP0872	450ml Aerosol	Clear	N/A

IMPORTANT: FOR PROFESSIONAL USE ONLY. Read full instructions before use.

This product contains hazardous materials and therefore appropriate personal protective equipment should always be used. Please refer to the label and consult the safety data sheet for full handling instructions and personal protection information. U-POL disclaims any liability where the user does not wear the recommended personal protective equipment. The above data is for information only and may change without prior notice. It is the Buyers responsibility to ensure the suitability of the products for their own use and check the information is up to date. The recommendation of use of our products and application in our technical data sheets are based on our knowledge and experience. These data sheets are available via your local distributor or via the U-POL website at WWW.U-POL.COM. U-POL is not responsible for the results obtained by others over whose methods we have no control and thereof U-POL is not liable for consequential or incidental damages including loss of profits.

U-POL US, Inc.

108 Commerce Way
Stockertown, PA 18083
WWW.U-POL.COM

US Sales

T: (610) 746 7081
F: (610) 743 8654
sales-us@u-pol.com

Rest of the World Sales

T: +44 (0)20 8492 5900
F: +44 (0)20 8150 5605
sales@u-pol.com

Technical

T: +44 (0)1933 230 310
F: +44 (0)1933 425 797
technicaldepartment@u-pol.com

EMERGENCY TELEPHONE:1-800-424-9300