WIZARDS DATA SHEET

MYSTIC CUT[™] Nano-Sphere Compound

AUTOMOTIVE

32 fl. oz. - 946 ml Part No.: 11048 6/case Net Wt. 15 lbs.

1 Gallon - 3.785 liters Part No.: 11052 4/case Net Wt. 35 lbs.

DESCRIPTION:

WIZARDS[®] MYSTIC CUT[™] is an aggressive cutting compound formulated with exclusive Nano-Sphere Technology for the new scratch resistant and hard to buff medium and high solid clears. MYSTIC CUT[™] is recommended for 1200/1500/2000 grit sand scratch removal without heavy swirling, powdering or dusting. Outstanding results are realized on all types of paint, including OEM and customs.

BENEFITS:

WOOL PAD

Progressive cutting can be achieved on all hard to buff clears without scratching, swirling, or leaving holograms. MYSTIC CUT[™] will cut through 1200 and finer grit sand scratches on all types of paint finishes, scratch resistant, medium/high solid clears, factory, custom - foreign and domestic.

With Super Nano abrasives, MYSTIC CUT[™] Compound will not throw abrasive splatter that will cause surface scratching on adjacent panels. MYSTIC CUT[™] can also be used successfully for most basic buffing jobs such as quickly removing car wash scratches and deep swirls found on neglected vehicles. <u>Cutting speed</u>, aggressiveness, and final gloss can be adjusted by proper pad choice coupled with buffer speed and operator technique.

FEATURES



- Progressive cutting action smoothly and quickly levels 1200/1500/2000 grit sand scratches on new hard to buff clears: scratch resistant, medium/ high solids.
- Fast action removal of deep swirls and car wash scratches; performs excellent on all types of paint and clears new, aged or neglected.
- Exclusive Super Nano abrasives will not scratch, swirl or leave holograms.
- Extreme show gloss finishing is easily achieved with the proper pad choice: blended wool for cut then foam for gloss.
- No dusting, no grit, water based system for fast and easy clean up.

HOW TO USE:

Always apply to clean, cool and dry surface. Apply generously to one spot, this allows for best initial cutting action on deeper scratches and can shorten buffing time. Avoid ribbons or specks over a large area. Run buffer at 1400-2000 RPM using a WIZARDS[®] #11203 Blended Wool Pad for a faster cut without pad scratches. Hold pad flat to the surface starting out slow, then speeding up applying adequate pressure to remove scratches. Continue with overlapping passes while moving slowly side to side. Reapply as needed but always lighten pressure on final passes and avoid dry buffing. Spur/wash pads as needed.

Follow up with WIZARDS[®] #11048 MYSTIC POLISH[™] Machine Glaze using #11206 Gray Foam Pad, or on black/dark colors continue with the softer, #11209 Foam Finish 2 Pad.

Orders: 800-356-7223 Local: 763-497-5155 • Fax: 763-497-5125 Website: www.WizardsProducts.com Email: sales@WizardsProducts.com RJ STAR, INC. • 11469 8th St. NE • Hanover, MN 55341



